


R 系列减速机有以下设计方案：

R series gear units are available in the following designs:




R (RF, RX, RXF) ...Y...

电机用户自配或配特殊电机时


需加联接法兰

When equipping the user's motor or the special one, the flange is required to be connected




R...Y...

底脚轴伸式安装斜齿轮减速机
Foot-mounted helical gear units with solid shaft



RF...Y...


法兰轴伸式安装斜齿轮减速机
Flange-mounted helical gear units with solid shaft



RS...


底脚轴伸式安装，轴输入的斜齿轮减速机
Foot-mounted, shaft input helical gear units with solid shaft

R




RFS...

法兰轴伸式，轴输入的斜齿轮减速机
Flange-mounted, shaft input helical gear units with solid shaft




R...R...Y...

底脚轴伸式安装组合型斜齿轮减速机
Foot-mounted combinatorial helical gear units with solid shaft




RF...R...Y...

法兰轴伸式组合型斜齿轮减速机
Flange-mounted combinatorial helical gear units with solid shaft




RS...R...

底脚轴伸式安装组合型，轴输入的斜齿轮减速机
Foot-mounted combinatorial, shaft input helical gear units with solid shaft




RFS...R...

法兰轴伸式组合型，轴输入的斜齿轮减速机
Flange-mounted combinatorial, shaft input helical gear units with solid shaft




RX...Y...

底脚轴伸式安装单级斜齿轮减速机
Foot-mounted single-stage helical gear units with solid shaft




RXF...Y...

法兰轴伸式安装单级斜齿轮减速机
Flange-mounted single-stage helical gear units with solid shaft



RXS...

底脚轴伸式安装，轴输入的单级斜齿轮减速机
Foot-mounted, shaft input single-stage helical gear units with solid shaft







RXFS...

法兰轴伸式，轴输入的单级斜齿轮减速机
Flange-mounted, shaft input single-stage helical gear units with solid shaft



型号与标记:



Type Designations:

R F 37-Y 0.55-4P-32.40-M1-270°-Φ200		R F 37-Y 0.55-4P-32.40-M1-270°-Φ200	
减速机类型		Gear units type	
结构形式		Structure	
规格		Size	
电机代号		Motor code	
电机功率、极数		Motor power、 pole	
传动比		Ratio	
安装形式		Mounting position	
电机接线盒位置		Position of the motor thermal box	
输出法兰外径		Outer diameter of output flange	
减速机类型: 斜齿轮硬齿面减速机		Gear units type: rigid tooth flank helical gear units	
结构形式: 普通轴伸式 (省略) 轴伸法兰式 F 普通轴伸式, 轴输入 S 轴伸法兰式, 轴输入 FS		Structure: Foot-mounted solid shaft output (-) Flange-mounted solid shaft output F Foot-mounted solid shaft output, shaft input S Flange-mounted solid shaft output, shaft input FS	
规格: (见选型参数表)		Size: (see selection table)	
电机代号: 普通 (更新) Y(Y2) 防 爆 B 直 流 Z 制 动 YEJ 多 速 D 变 频 YVP 电磁调速 YCT 冶金起重 R 变频制动 YVPJ 辊 道 G		Motor code: Ordinary(renew) Y(Y2) Flame-proof B Direct current Z Brake YEJ Multi-speed D Variable frequency YVP Electromagnetism speed modulation YCT Hoisting in metallurgy R Variable frequency and brake YVPJ Roller tables G	
电机功率、极数: (见选型参数表)		Motor power、 pole : (see selection table)	
传动比: (见选型参数表)		Ratio: (see selection table)	
安装形式: M1、M2、M3、M4、M5、M6 (见第13页)		Mounting position: M1、M2、M3、M4、M5、M6(see page 13)	
电机接线盒位置: 0°、90°、180°、270° (见第12页)		Position of the motor thermal box: 0°、90°、180°、270° (see page 12)	
输出法兰外径: (见外型安装尺寸图)底脚安装时省略		Outer diameter of output flange: (See the chart of mouting dimension sheets-overview) It will be omitted when foot mouting.	
电机接线盒位置: Position of the motor thermal box:			
   			
0° 90° 180° 270°			



安装形式:

Mounting position:



R

输入功率及许用转矩

Input power rating and permissible torque

规格 Size	17	27	37	47	57	67	77	87	97	107	137	147	167
结构形式 Structure	R						RF						
输入功率 Input power rating (kW)	0.18~0.75	0.18~3	0.18~3	0.18~5.5	0.18~7.5	0.18~7.5	0.18~11	0.55~22	0.55~30	2.2~45	5.5~55	11~90	11~160
传动比 Ratio	3.83~ 74.84	3.37~ 135.09	3.33~ 134.82	3.83~ 176.88	4.39~ 186.89	4.29~ 199.81	5.21~ 195.24	5.36~ 246.54	4.49~ 289.74	5.06~ 249.16	5.15~ 222.60	5.00~ 163.31	10.24~ 229.71
许用转矩 Permissible torque (N.m)	85	130	200	300	450	600	820	1550	3000	4300	8000	13000	18000

规格 Size	37	57	67	77	87	97	107	127	157
结构形式 Structure	RX				RXF				
输入功率 (kW) Input power rating	0.18~1.1	0.18~5.5	0.18~7.5	1.1~11	3~22	5.5~30	7.5~45	7.5~90	11~132
传动比 Ratio	1.62~4.43	1.3~5.5	1.4~6.07	1.42~8.00	1.39~8.65	1.42~8.23	1.44~6.63	1.51~6.2	1.57~6.2
许用转矩 (N.m) Permissible torque	20	70	135	215	400	600	830	1110	1680

减速机重量

Gear unit weight

规格 Size	R17	R27	R37	R47	R57	R67	R77	R87	R97	R107	R137	R147	R167
重量 (kg) Weight	4	5.5	8.5	10	18	25	36	63	101	153	220	400	700
机型号 Gear unit type	RX37	RX57	RX67	RX77	RX87	RX97	RX107	RX127	RX157				
重量 (kg) Weight	5	8	14	23	39	70	100	150	250				

所注重量为平均值, 仅供参考

The weights are mean values, only for reference.

润滑油量表
Lubrication table

规格 Size	润滑油量 (升) Fill quantity in liters					
	M1 ¹⁾	M2 ¹⁾	M3	M4	M5	M6
R17	0.25	0.6	0.35	0.6	0.35	0.35
R27	0.25/0.4	0.7	0.4	0.7	0.4	0.4
R37	0.3/1	0.9	1	1.1	0.8	1
R47	0.7/1.5	1.6	1.5	1.7	1.5	1.5
R57	0.8/1.7	1.9	1.7	2.1	1.7	1.7
R67	1.1/2.3	2.6/3.5	2.8	3.2	1.8	2
R77	1.2/3	3.8/4.3	3.6	4.3	2.5	3.4
R87	2.3/6	6.7/8.4	7.2	7.7	6.3	6.5
R97	4.6/9.8	11.7/14	11.7	13.4	11.3	11.7
R107	6/13.7	16.3	16.9	19.2	13.2	15.9
R137	10/25	28	29.5	31.5	25	25
R147	15.4/40	46.5	48	52	39.5	41
R167	27/70	82	78	88	66	69

规格 Size	润滑油量 (升) Fill quantity in liters					
	M1 ¹⁾	M2 ¹⁾	M3	M4	M5	M6
RF17	0.25	0.6	0.35	0.6	0.35	0.35
RF27	0.25/0.4	0.7	0.4	0.7	0.4	0.4
RF37	0.4/1	0.9	1	1.1	0.8	1
RF47	0.75/1.5	1.6	1.5	1.7	1.5	1.5
RF57	0.8/1.7	1.8	1.7	2	1.7	1.7
RF67	1.2/2.5	2.7/3.6	2.7	3.1	1.9	2.1
RF77	1.2/2.6	3.8/4.1	3.3	4.1	2.4	3
RF87	2.4/6	6.8/7.9	7.1	7.7	6.3	6.4
RF97	5.1/10.2	11.9/14	11.2	14	11.2	11.8
RF107	6.3/14.9	15.9	17	19.2	13.1	15.9
RF137	9.5/25	27	29	32.5	25	25
RF147	16.4/42	47	48	52	42	42
RF167	26/70	82	78	88	65	71

规格 Size	润滑油量 (升) Fill quantity in liters					
	M1	M2	M3	M4	M5	M6
RX37/RXF37	0.45/0.4	0.6	1.1/0.9	1.1/0.9	0.7/0.6	0.7/0.6
RX57/RXF57	0.6/0.5	0.8	1.3/1.1	1.3/1.1	0.9/0.7	0.9/0.7
RX67/RXF67	0.8/0.7	0.8	1.7/1.5	1.9/1.7	1.1/1	1.1/1
RX77/RXF77	1.1/0.9	1.5	2.6/2.4	2.7/2.5	1.6	1.6
RX87/RXF87	1.7/1.6	2.5	4.8/4.9	4.8/4.7	2.9	2.9
RX97/RXF97	2.1	3.4/3.6	7.4/7.1	7	4.8	4.8
RX107/RXF107	3.9/3.1	5.6/5.9	11.6/11.2	11.9/10.5	7.7/7.2	7.7/7.2
RX127/RXF127	5.6/5.9	11.6/11.2	21.9/20.5	22.7/22.2	9.7/9.2	9.7/9.2
RX157/RXF157	11.6/11.2	21.9/20.5	31.3/30.5	32.7/32.2	13.2/12.7	13.2/12.7

注：1) 表示减速机为组合型时低速级所加油量为大值。

Notes: 1) The large gear unit of multi-stage gear units must be filled with the larger oil volume.



输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f_B	机 型 号 Type Type	极 数 Pole p	输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f_B	机 型 号 Type Type	极 数 Pole p
0.18kW						0.18kW					
0.16	9293	8443	1.31	R 147R77 RF147R77	4	1.6	944	858	0.82	R 77R37 RF77R37	4
0.19	8042	7307	1.52			1.7	904	821	0.85		
0.22	7096	6447	1.72			1.8	833	757	0.93		
0.25	6128	5568	1.99			1.9	803	730	0.96		
0.29	5300	4815	2.31			2.1	739	671	1.04		
0.32	4760	4325	2.57			2.2	711	646	1.08		
0.38	4038	3669	3.03			2.4	628	571	1.23		
0.43	3553	3228	3.44	R 137R77 RF137R77	4	2.5	602	547	1.28	R 67R37 RF67R37	4
0.16	9668	8784	0.8			2.9	525	477	1.47		
0.19	8232	7479	0.91			3.3	469	426	1.64		
0.22	7057	6412	1.07			3.8	402	365	1.92		
0.24	6421	5834	1.17			4.5	341	310	2.26		
0.28	5504	5001	1.37			2.4	628	571	0.90		
0.30	5183	4709	1.45			2.5	617	561	0.91		
0.32	4803	4364	1.57	R 107R77 RF107R77	4	2.9	532	483	1.06	R 57R37 RF57R37	4
0.35	4323	3928	1.74			3.2	482	438	1.17		
0.40	3868	3514	1.94			3.6	427	388	1.32		
0.42	3674	3338	2.05			4.1	370	336	1.53		
0.47	3224	2929	2.33			4.8	316	287	1.79		
0.31	4881	4435	0.83			5.5	281	255	2.01		
0.36	4260	3870	0.95	R 97R57 RF97R57	4	3.0	518	471	0.82	R 37R17 RF37R17	4
0.42	3634	3302	1.11			3.1	488	443	0.87		
0.46	3299	2997	1.23			3.4	451	410	0.94		
0.53	2885	2621	1.40			3.9	395	359	1.07		
0.62	2479	2252	1.63			4.3	357	324	1.19		
0.68	2246	2041	1.80			4.4	351	319	1.20		
0.71	2169	1971	1.86			4.8	319	290	1.33		
0.77	1995	1813	2.03	R 87R57 RF87R57	4	5.2	294	267	1.44	R 77 RF77	6
0.88	1747	1587	2.31			5.3	288	262	1.47		
1.0	1529	1389	2.64			5.7	271	246	1.56		
1.1	1338	1216	3.02			5.8	265	241	1.59		
0.51	2996	2722	0.94			6.3	242	220	1.75		
0.52	2937	2668	0.96			6.5	237	215	1.79		
0.60	2544	2311	1.11			7.4	207	188	2.04		
0.62	2471	2245	1.14	R 77R37 RF77R37	4	8.7	175	159	2.42		
0.67	2287	2078	1.23			4.6	331	301	0.85		
0.69	2219	2016	1.27			5.5	281	255	1.00		
0.80	1907	1733	1.48			6.1	251	228	1.12		
0.86	1786	1623	1.58			7.1	215	195	1.31		
0.97	1578	1434	1.79			6.2	249	226	0.8		
1.2	1328	1207	2.12			6.9	222	202	0.85		
1.3	1193	1084	2.36	R 27R17 RF27R17	4	7.0	219	199	0.86		
1.5	1028	934	2.74			7.8	197	179	0.95		
1.6	966	878	2.92			8.9	173	157	1.09		
1.8	831	755	3.39			9.1	172	156	1.11		
0.79	1912	1737	0.8			9.3	165	150	1.14		
0.80	1907	1733	0.85			9.9	155	141	0.8		
0.91	1677	1524	0.87			10	149	135	0.82		
0.93	1639	1489	0.89			11	136	124	0.90		
1.0	1535	1395	0.95			12	130	118	0.94		
1.1	1356	1232	1.07			13	121	110	1.01		
1.2	1260	1145	1.16			14	114	104	1.07		
1.3	1141	1037	1.28			15	103	94	1.18		
1.5	1025	931	1.42	R 77 RF77	6	4.4	371	195.24	2.1		
1.6	972	883	1.50			5.1	317	166.59	2.4		
1.7	883	802	1.65			5.8	277	145.67	2.8		
1.8	852	774	1.71			6.1	263	138.39	2.9		
						7.0	231	121.42	3.3		

R



R

输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f _s	机 型 号 Type Type	极 数 Pole p	输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f _s	机 型 号 Type Type	极 数 Pole p
0.18kW						0.18kW					
7.1	227	195.24	3.4	R 77 RF77	4	11	144	123.91	0.85	R 27 RF27	4
8.3	194	166.59	4.0			13	123	105.49	1.00		
9.5	169	145.67	4.6			15	106	90.96	1.16		
10	161	138.39	4.8			16	99	84.78	1.24		
4.3	380	199.81	1.48	R 67 RF67	6	19	86	74.11	1.42		
4.6	350	184.07	1.61			20	81	69.47	1.51		
5.4	301	158.14	1.88			23	71	61.30	1.71		
6.2	262	137.67	2.2			25	65	55.87	1.88		
6.6	245	128.97	2.3			29	56	48.17	2.2		
7.5	217	113.94	2.6			31	52	44.90	2.3		
8.0	201	105.83	2.8			35	46	39.25	2.7		
8.9	182	95.91	3.1			38	44	36.79	2.8		
9.9	164	86.11	3.4			43	39	32.47	3.2		
11	141	74.17	4.0			48	35	28.78	3.5		
12	133	69.75	4.3			49	34	28.37	3.6		
7.0	232	199.81	2.4	R 67 RF67	4	53	31	26.09	3.9		
7.6	214	184.07	2.6			57	29	24.47	4.2		
8.8	184	158.14	3.1			62	26	22.32	4.6		
10	160	137.67	3.5			72	23	19.35	5.3		
11	150	128.97	3.8			77	21	18.08	5.7		
12	132	113.94	4.3			89	19	15.63	6.6		
13	123	105.83	4.6			105	16	13.28	7.8		
4.5	355	186.89	1.19	R 57 RF57	6	37	45	23.13	1.78	R 17 RF17	6
4.9	327	172.17	1.29			40	41	21.22	1.94		
5.7	281	147.92	1.50			47	35	18.06	2.28		
6.6	245	128.77	1.73			19	87	74.84	0.92	R 17 RF17	4
7.0	229	120.63	1.84			22	75	64.52	1.07		
7.4	217	186.89	1.95	R 57 RF57	4	23	70	60.14	1.14		
8.1	200	172.17	2.1			26	61	52.57	1.31		
9.4	172	147.92	2.5			28	57	49.28	1.39		
11	150	128.77	2.8			32	51	43.49	1.58		
12	140	120.63	3.0			34	47	40.49	1.70		
13	124	106.58	3.4			39	41	35.40	1.94		
14	115	98.99	3.7			42	39	33.18	2.07		
15	104	89.71	4.1			47	34	29.28	2.3		
7.9	206	176.88	1.37	R 47 RF47	4	54	30	25.96	2.6		
8.5	189	162.94	1.49			60	27	23.13	2.9		
9.9	163	139.99	1.73			63	26	22.06	3.1		
11	142	121.87	1.99			66	25	21.22	3.2		
12	133	114.17	2.1			77	21	18.06	3.7		
14	117	100.86	2.4			89	18	15.57	4.3		
15	109	93.68	2.6			96	17	14.52	4.6		
16	99	84.90	2.9			110	15	12.69	5.3		
18	89	76.23	3.2			117	14	11.89	5.7		
6.9	235	123.66	0.80	R 37 RF37	6	132	12	10.5	5.9		
8.1	200	105.28	0.94			149	11	9.31	6.1		
9.4	173	90.77	1.09			176	10	7.91	6.2		
10	161	84.61	1.17			184	9	7.55	6.5		
10	157	134.82	1.20	R 37 RF37	4	197	8	7.04	7.0		
11	144	123.66	1.31			226	7.5	6.15	7.2		
13	122	105.28	1.54			241	7	5.76	7.3		
15	106	90.77	1.78			273	6	5.09	7.9		
16	98	84.61	1.91			308	5	4.51	8.4		
19	86	73.96	2.2			363	4.5	3.83	10		
20	81	69.33	2.3			140	12	6.07	3.4	RX 67 RXF67	6
23	71	61.18	2.6			164	10	5.18	6.9		
25	65	55.76	2.9			188	9.0	4.53	8.6		
29	56	48.08	3.1			198	8.5	4.30	8.8		



输出转速	输出扭矩	传动比	使用系数	机 型 号	极 数	输出转速	输出扭矩	传动比	使用系数	机 型 号	极 数				
Output speed	Output torque	Ratio	Service factor	Type	Pole	Output speed	Output torque	Ratio	Service factor	Type	Pole				
r/min	Nm	i	f _B	Type	p	r/min	Nm	i	f _B	Type	p				
0.18kW						0.25kW									
229	7.4	6.07	5.5	RX 67 RXF67	4	0.69	3082	2016	0.92	R 97R57 RF97R57	4				
268	6.3	5.18	11			0.76	2787	1823	1.01						
307	5.5	4.53	13			0.80	2649	1733	1.06						
323	5.2	4.30	14			0.86	2481	1623	1.14						
369	4.6	3.77	18			0.88	2420	1583	1.17						
434	3.9	3.20	24			1.0	2134	1396	1.32						
481	3.5	2.89	28			1.1	1877	1228	1.50						
547	3.1	2.54	36			1.3	1633	1068	1.73						
579	2.9	2.40	40	RX 57 RXF57	4	1.5	1432	937	1.97	R 87R57 RF87R57	4				
681	2.5	2.04	51			1.7	1260	824	2.2						
155	11	5.50	3.36			1.9	1127	737	2.5						
168	10	5.07	3.37			2.2	965	631	2.9						
195	8.6	4.35	7.4			1.2	1750	1145	0.83						
224	7.5	3.79	8.5			1.3	1585	1037	0.92						
253	6.7	5.50	5.50			1.5	1423	931	1.02						
274	6.1	5.07	5.51			1.6	1350	883	1.08						
320	5.3	4.35	12			1.7	1226	802	1.19						
367	4.6	3.79	14			1.8	1183	774	1.23						
392	4.3	3.55	15	RX 57 RXF57	4	2.0	1044	683	1.40	R 77R37 RF77R37	4				
443	3.8	3.14	16			2.3	916	599	1.59						
478	3.5	2.91	18			2.6	803	525	1.82						
527	3.2	2.64	20			3.1	694	454	2.1						
586	2.9	2.37	23			5.2	408	267	3.6						
681	2.5	2.04	26			2.4	873	571	0.88						
724	2.3	1.92	28			2.5	836	547	0.92						
842	2.0	1.65	32			2.9	729	477	1.06						
426	4	3.26	3.80			RX 37 RXF37	4	3.3	651			426	1.18	R 67R37 RF67R37	4
527	3	2.64	4.69					3.8	556			364	1.39		
0.25kW								4.5	477	312	1.62				
0.14	14894	9743	0.82	4.6	474			310	1.63						
0.16	12907	8443	0.95	5.6	379			248	2.03						
0.19	11170	7307	1.09	6.3	335			219	2.3						
0.22	9855	6447	1.24	3.6	593			388	0.95						
0.25	8512	5568	1.44	3.9	549			359	1.03						
0.29	7361	4815	1.66	4.1	514			336	1.10						
0.32	6612	4325	1.85	4.5	474			310	1.19						
0.38	5609	3669	2.18	R 147R77 RF147R77	4	4.8	439	287	1.29						
0.43	4935	3228	2.48			5.3	404	264	1.40						
0.49	4331	2833	2.82			5.5	390	255	1.45						
0.24	8918	5834	0.84			5.9	359	235	1.57						
0.28	7645	5001	0.98			6.1	350	229	1.61						
0.30	7199	4709	1.04			6.9	307	201	1.84						
0.32	6671	4364	1.13			7.1	298	195	1.89						
0.35	6142	4018	1.22			7.7	277	181	2.0						
0.37	6005	3928	1.25			8.1	263	172	2.15						
0.40	5372	3514	1.40			9.0	235	154	2.40						
0.42	5103	3338	1.47	R 137R77 RF137R77	4	4.3	495	324	0.85	R 57R37 RF57R37	4				
0.47	4478	2929	1.68			4.4	488	319	0.87						
0.52	4063	2658	1.85			4.8	443	290	0.95						
0.58	3687	2414	2.0			5.2	408	267	1.04						
0.67	3169	2073	2.4			5.3	401	262	1.06						
0.76	2811	1839	2.7			5.7	376	246	1.12						
0.99	2136	1397	3.5			5.8	368	241	1.15						
1.1	1874	1226	4.0			6.3	336	220	1.26						
0.46	4609	3015	0.88			6.5	329	215	1.29						
0.71	3013	1971	1.34			7.6	280	183	1.51						
0.77	2772	1813	1.46	8.6	246	161	1.72								
0.88	2426	1587	1.67	10	211	138	2.0								
1.0	2123	1389	1.90	R 107R77 RF107R77	4	6.1	349	228	0.81	R 47R37 RF47R37	4				
1.1	1859	1216	2.2			7.1	298	195	0.95						
1.5	1417	927	2.9			7.6	278	182	1.01						
1.7	1241	812	3.3			9.0	235	154	1.20						



输出转速	输出扭矩	传动比	使用系数	机 型 号	极 数	输出转速	输出扭矩	传动比	使用系数	机 型 号	极 数		
Output speed	Output torque	Ratio	Service factor	Type	Pole	Output speed	Output torque	Ratio	Service factor	Type	Pole		
r/min	Nm	i	f _B	Type	p	r/min	Nm	i	f _B	Type	p		
0.25kW						0.25kW							
8.9	238	156	0.79	R 37R17 RF37R17	4	7.4	308	186.89	1.37	R 57 RF57	4		
9.3	229	150	0.82			8.1	284	172.17	1.49				
10	206	135	0.91			9.4	244	147.92	1.73				
11	194	127	0.97			11	212	128.77	1.99				
12	168	110	1.12			12	199	120.63	2.1				
13	159	104	1.18			13	176	106.58	2.4				
14	144	94	1.31			14	163	98.99	2.6				
15	138	90	1.37			15	148	89.71	2.9				
						17	133	80.55	3.2				
						20	114	69.23	3.7				
2.2	1029	289.60	2.7	R 97 RF97	8	7.9	292	176.88	0.97	R 47 RF47	4		
2.5	913	256.89	3.1			8.5	269	162.94	1.05				
2.7	856	240.83	3.3			9.9	231	139.99	1.22				
3.0	767	215.94	3.7			11	201	121.87	1.40				
2.6	876	246.54	1.66	R 87 RF87	8	12	188	114.17	1.50				
3.0	769	216.54	1.89			14	166	100.86	1.70				
3.1	731	205.71	1.99			15	154	93.68	1.83				
3.5	646	181.77	2.3			16	140	84.90	2.0				
3.9	592	166.59	1.30	R 77 RF77	8	18	126	76.23	2.2				
4.4	518	145.67	1.49			20	113	68.54	2.5				
4.7	492	138.39	1.57			22	106	64.21	2.7				
5.3	431	121.42	1.79			25	94	56.73	3.0				
4.4	526	195.24	1.46	R 77 RF77	6	26	87	52.69	3.2				
5.1	449	166.59	1.72			29	79	47.75	3.6				
5.8	393	145.67	1.96			10	222	134.82	0.85	R 37 RF37	4		
7.1	322	195.24	2.4	R 77 RF77	4	11	204	123.66	0.92				
8.3	275	166.59	2.8			13	175	105.28	1.08				
9.5	240	145.67	3.2			15	150	90.77	1.26				
10	228	138.39	3.4			16	140	84.61	1.35				
11	200	121.42	3.8			19	122	73.96	1.54				
4.1	562	158.14	1.00	R 67 RF67	8	20	114	69.33	1.64				
4.7	489	137.67	1.15			23	101	61.18	1.86				
5.0	458	128.97	1.23			25	92	55.76	2.0				
5.7	405	113.94	1.39			29	79	48.08	2.4				
4.3	539	199.81	1.05	R 67 RF67	6	31	74	44.81	2.5				
4.6	496	184.07	1.14			35	65	39.17	2.9				
5.4	426	158.14	1.32			38	61	36.72	3.1				
6.2	371	137.67	1.52			43	53	32.40	3.5				
6.6	348	128.97	1.62			16	140	84.78	0.87	R 27 RF27	4		
7.5	307	113.94	1.84			19	122	74.11	1.00				
8.0	285	105.83	1.98			20	115	69.47	1.07				
7.0	329	199.81	1.71	R 67 RF67	4	23	101	61.30	1.21				
7.6	304	184.07	1.86			25	92	55.87	1.33				
8.8	261	158.14	2.2			29	79	48.17	1.54				
10	227	137.67	2.5			31	74	44.90	1.65				
11	213	128.97	2.7			35	65	39.25	1.89				
12	188	113.94	3.0			38	61	36.79	2.0				
13	175	105.83	3.2			43	54	32.47	2.3				
14	158	95.91	3.6			48	48	28.78	2.5				
16	142	86.11	4.0			49	47	28.37	2.6				
4.5	504	186.89	0.84	R 57 RF57	6	53	43	26.09	2.8				
4.9	464	172.17	0.91			57	40	24.47	3.0				
5.7	399	147.92	1.06			62	37	22.32	3.3				
6.6	347	128.77	1.22			72	32	19.35	3.8				
7.0	325	120.63	1.30			77	30	18.08	4.1				
8.0	287	106.58	1.47			89	26	15.63	4.7				
8.6	267	98.99	1.58			105	22	13.28	5.6				
						117	20	11.86	6.2				
						137	17	10.13	6.9				
						148	16	9.41	7.4				
						170	14	8.16	8.1				
						182	13	7.63	8.4				
						211	11	6.59	9.2				
						248	9.0	5.60	10				
						278	8.2	5.00	11				
						326	7.0	4.27	12				
						348	7.0	4.00	12				
						412	6.0	3.37	13				

R



输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f _B	机 型 号 Type Type	极 数 Pole p	输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f _B	机 型 号 Type Type	极 数 Pole p
0.25kW						0.37kW					
26	87	52.57	0.92	R 17 RF17	4	0.19	16532	7307	0.80	R 147R77 RF147R77	4
28	81	49.28	0.98			0.22	14586	6447	0.84		
32	72	43.49	1.11			0.25	12597	5568	0.97		
34	67	40.49	1.20			0.29	10894	4815	1.12		
39	58	35.40	1.37			0.32	9785	4325	1.25		
42	55	33.18	1.46			0.38	8301	3669	1.47		
47	48	29.28	1.65			0.43	7303	3228	1.67		
54	43	25.96	1.87			0.49	6410	2833	1.91		
60	38	23.13	2.1			0.32	9873	4364	0.76	R 137R77 RF137R77	4
63	36	22.06	2.2			0.35	8887	3928	0.85		
66	35	21.22	2.3			0.40	7950	3514	0.95		
77	30	18.06	2.7			0.42	7552	3338	1.00		
89	26	15.57	3.1			0.47	6627	2929	1.13		
96	24	14.52	3.3			0.52	6014	2658	1.25		
110	21	12.69	3.8			0.56	5620	2484	1.34		
117	20	11.89	4.1			0.58	5457	2412	1.38		
132	17	10.5	4.2			0.62	5072	2242	1.48		
149	15	9.31	4.4			0.67	4690	2073	1.60		
176	13	7.91	4.5			0.76	4161	1839	1.81		
184	12	7.55	4.7			0.99	3161	1397	2.4		
197	11	7.04	5.0			1.1	2774	1226	2.7		
226	10	6.15	5.2			1.3	2466	1090	3.0		
241	9	5.76	5.3			1.5	2152	951	3.5		
273	8	5.09	5.7			0.68	4618	2041	0.88	R 107R77 RF107R77	4
308	7	4.51	6.1			0.71	4459	1971	0.91		
363	6	3.83	6.7			0.77	4102	1813	0.99		
140	16	6.07	2.5	RX 67 RXF67	6	0.83	3785	1673	1.07		
164	14	5.18	4.9			0.88	3591	1587	1.13		
188	13	4.53	6.2			0.91	3464	1531	1.17		
198	12	4.30	6.4			1.0	3145	1390	1.29		
229	10	6.07	4.0	RX 67 RXF67	4	1.1	2751	1216	1.47		
268	9	5.18	8.1			1.2	2701	1194	1.50		
307	8	4.53	10			1.3	2360	1043	1.71		
323	7	4.30	10			1.5	2097	927	1.93		
369	6	3.77	13			1.7	1837	812	2.2		
434	5.5	3.20	17			0.97	3244	1434	0.87	R 97R57 RF97R57	4
481	5	2.89	20			1.0	3158	1396	0.89		
547	4.5	2.54	26			1.1	2778	1228	1.02		
579	4	2.40	29			1.2	2731	1207	1.03		
681	3	2.04	37			1.3	2453	1084	1.15		
155	15	5.50	2.4	RX 57 RXF57	6	1.4	2416	1068	1.17		
168	14	5.07	2.4			1.5	2120	937	1.33		
195	12	4.35	5.3			1.7	1864	824	1.51		
224	10	3.79	6.2			1.9	1667	737	1.69		
253	9.3	5.50	4.0	RX 57 RXF57	4	2.2	1428	631	1.98		
274	8.5	5.07	4.0			3.2	973	430	2.9		
320	7.3	4.35	9.0			3.7	857	379	3.3		
367	6.4	3.79	10			4.1	760	336	3.7		
392	6.0	3.55	11			1.7	1814	802	0.80	R 87R57 RF87R57	4
443	5.3	3.14	12			1.8	1751	774	0.83		
478	4.9	2.91	13			1.9	1706	754	0.85		
527	4.4	2.64	15			2.0	1545	683	0.94		
586	4.0	2.37	16			2.1	1468	649	0.99		
681	3.4	2.04	19			2.3	1355	599	1.08		
724	3.2	1.92	20			2.5	1217	538	1.20		
842	2.8	1.65	23			2.6	1188	525	1.23		
370	6	3.76	2.37	RX 37 RXF37	4	2.9	1068	472	1.36		
426	5.5	3.26	2.73			3.1	1027	454	1.42		
456	5	3.05	2.92			3.5	905	400	1.61		
527	4.5	2.64	3.38			3.9	817	361	1.78		
621	4	2.24	3.98			5.2	604	267	2.4		
695	3.5	2.00	4.46			5.9	532	235	2.7		
813	3	1.71	5.21								
869	2.5	1.60	5.57								

R



输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f_s	机 型 号 Type Type	极 数 Pole p	输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f_s	机 型 号 Type Type	极 数 Pole p
0.37kW						0.37kW					
3.3	964	426	0.80	R 77R37 RF77R37	4	6.6	503	128.77	0.84	R 57 RF57	6
3.8	824	364	0.94			7.0	471	120.63	0.90		
4.3	740	327	1.04			8.0	416	106.58	1.02		
4.5	701	310	1.10			8.6	387	98.99	1.09		
5.6	561	248	1.37			7.4	447	186.89	0.95	R 57 RF57	4
6.3	495	219	1.56			8.1	411	172.17	1.03		
7.4	425	188	1.81			9.4	353	147.92	1.20		
8.6	367	162	2.1			11	308	128.77	1.37		
9.8	321	142	2.4			12	288	120.63	1.47		
4.8	649	287	0.87	R 67R37 RF67R37	4	13	255	106.58	1.66		
5.5	577	255	0.98			14	237	98.99	1.79		
6.1	518	229	1.09			15	214	89.71	1.97		
7.1	441	195	1.28			17	192	80.55	2.2		
2.5	1323	256.89	2.1	R 97 RF97	8	20	165	69.23	2.6		
2.7	1240	240.83	2.3			21	155	64.85	2.7		
3.0	1112	215.94	2.5			24	137	57.29	3.1		
3.5	958	185.97	2.9			26	127	53.22	3.3		
2.9	1132	289.60	2.5	R 97 RF97	6	29	115	48.23	3.7		
3.3	1004	256.89	2.8			9.9	335	139.99	0.84	R 47 RF47	4
3.5	941	240.83	3.0			11	291	121.87	0.97		
3.9	844	215.94	3.3			12	273	114.17	1.03		
3.0	1115	216.54	1.31	R 87 RF87	8	14	241	100.86	1.17		
3.1	1059	205.71	1.38			15	224	93.68	1.26		
3.5	936	181.77	1.6			16	203	84.90	1.39		
3.4	963	246.54	1.51	R 87 RF87	6	18	182	76.23	1.55		
3.9	846	216.54	1.72			20	164	68.54	1.72		
4.1	804	205.71	1.81			22	153	64.21	1.84		
4.7	710	181.77	2.1			25	136	56.73	2.1		
5.5	607	155.34	2.4			26	126	52.69	2.2		
6.0	556	142.41	2.6			29	114	47.75	2.5		
4.4	750	145.67	1.03	R 77 RF77	8	32	102	42.87	2.6		
4.7	713	138.39	1.08			38	88	36.93	2.7		
5.3	625	121.42	1.23			40	83	34.73	2.8		
5.1	651	166.59	1.18	R 77 RF77	6	41	81	33.79	3.2		
5.8	569	145.67	1.35			45	74	31.12	3.4		
6.1	541	138.39	1.43			52	64	26.74	4.4		
7.1	467	195.24	1.65	R 77 RF77	4	60	56	23.28	5.1		
8.3	398	166.59	1.94			64	52	21.81	5.4		
9.5	348	145.67	2.2			15	217	90.77	0.87	R 37 RF37	4
10	331	138.39	2.3			16	202	84.61	0.93		
11	290	121.42	2.7			19	177	73.96	1.06		
13	246	102.99	3.1			20	166	69.33	1.13		
15	222	92.97	3.47			23	146	61.18	1.29		
5.4	618	158.14	0.91	R 67 RF67	6	25	133	55.76	1.41		
6.2	538	137.67	1.05			29	115	48.08	1.64		
6.6	504	128.97	1.12			31	107	44.81	1.76		
7.5	445	113.94	1.27			35	94	39.17	2.0		
7.0	477	199.81	1.18	R 67 RF67	4	38	88	36.72	2.1		
7.6	440	184.07	1.28			43	77	32.40	2.4		
8.8	378	158.14	1.49			48	69	28.73	2.7		
10	329	137.67	1.71			49	68	28.32	2.8		
11	308	128.97	1.83			53	62	26.03	2.9		
12	272	113.94	2.1			57	58	24.42	3.2		
13	253	105.83	2.2			62	53	22.27	3.5		
14	229	95.91	2.5			72	46	19.31	4.1		
16	206	86.11	2.7			77	43	18.05	4.4		
19	177	74.17	3.2			89	38	15.60	4.9		
20	167	69.75	3.4			105	32	13.25	5.5		
23	146	61.26	3.9			117	29	11.83	6.0		
24	136	56.89	4.1								

R



输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f _s	机 型 号 Type Type	极 数 Pole p	输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f _s	机 型 号 Type Type	极 数 Pole p
0.55kW						0.55kW					
1.5	3151	937	0.89	R 97R57 RF97R57	4	8.8	562	158.14	1.00	R 67 RF67	4
1.7	2771	824	1.02			10	489	137.67	1.15		
1.9	2479	737	1.14			11	458	128.97	1.23		
2.2	2122	631	1.33			12	405	113.94	1.39		
2.5	1883	560	1.50			13	376	105.83	1.50		
2.9	1628	484	1.73			14	341	95.91	1.66		
3.2	1446	430	1.95			16	306	86.11	1.84		
3.7	1275	379	2.2			19	263	74.17	2.1		
4.1	1130	336	2.5			20	248	69.75	2.3		
4.7	995	296	2.8			23	218	61.26	2.6		
5.6	837	249	3.4			24	202	56.89	2.8		
2.6	1766	525	0.83	R 87R57 RF87R57	4	12	428	120.63	0.99	R 57 RF57	4
2.9	1587	472	0.92			13	379	106.58	1.12		
3.1	1527	454	0.95			14	352	98.99	1.20		
3.5	1345	400	1.08			15	319	89.71	1.33		
3.6	1332	396	1.09			17	286	80.55	1.48		
3.9	1214	361	1.20	R 77R37 RF77R37	4	20	246	69.23	1.72		
4.0	1180	351	1.23			21	230	64.85	1.84		
4.6	1026	305	1.42			24	203	57.29	2.1		
5.1	925	275	0.83			26	189	53.22	2.2		
5.9	794	236	0.97			29	171	48.23	2.5		
6.3	743	221	1.04	R 97 RF97	8	32	154	43.30	2.8		
7.8	599	178	1.29			37	132	37.30	3.2		
2.6	1893	256.89	1.50			40	125	35.07	3.4		
2.8	1775	240.83	1.59			53	93	26.31	4.5		
3.1	1591	215.94	1.77			56	89	24.99	4.8		
2.9	1682	289.60	1.68	R 97 RF97	6	63	78	21.93	5.4		
3.3	1492	256.89	1.90			75	66	18.60	6.4		
3.5	1399	240.83	2.0			15	333	93.68	0.85	R 47 RF47	4
3.9	1254	215.94	2.2			16	302	84.90	0.94		
4.8	1029	289.60	2.7	R 97 RF97	4	18	271	76.23	1.04		
5.4	912	256.89	3.1			20	243	68.54	1.16		
5.8	855	240.83	3.3			22	228	64.21	1.24		
6.4	767	215.94	3.7			25	202	56.73	1.40		
3.6	1375	246.54	1.06	R 87 RF87	6	26	187	52.69	1.51		
4.1	1208	216.54	1.21			29	170	47.75	1.66		
4.3	1148	205.71	1.27			32	152	42.87	1.85		
4.9	1014	181.77	1.44			38	131	36.93	2.1		
5.7	867	155.34	1.68			40	123	34.73	2.3		
5.6	876	246.54	1.66	R 87 RF87	4	47	106	29.88	2.7		
6.4	769	216.54	1.89			52	95	26.74	3.0		
6.8	731	205.71	2.0			60	83	23.28	3.4		
7.6	646	181.77	2.3			64	77	21.81	3.6		
8.9	552	155.34	2.6			23	217	61.18	0.87	R 37 RF37	4
9.8	506	142.41	2.9			25	198	55.76	0.95		
11	444	124.97	3.3			29	171	48.08	1.10		
12	421	118.43	3.5			31	159	44.81	1.18		
13	368	103.65	4.0			35	139	39.17	1.35		
8.3	592	166.59	1.30	R 77 RF77	4	38	130	36.72	1.44		
9.5	517	145.67	1.49			43	115	32.40	1.63		
10	492	138.39	1.57			48	102	28.73	1.84		
11	431	121.42	1.79			57	87	24.42	2.2		
13	366	102.99	2.1			62	79	22.27	2.4		
15	330	92.97	2.3			72	69	19.31	2.7		
17	291	81.80	2.7			77	64	18.05	2.9		
18	274	77.24	2.8			89	55	15.60	3.4		
21	234	65.77	3.3			105	47	13.25	4.0		
						117	42	11.83	4.5		



输出转速	输出扭矩	传动比	使用系数	机 型 号	极 数	输出转速	输出扭矩	传动比	使用系数	机 型 号	极 数		
Output speed	Output torque	Ratio	Service factor	Type	Pole	Output speed	Output torque	Ratio	Service factor	Type	Pole		
r/min	Nm	i	f _B	Type	p	r/min	Nm	i	f _B	Type	p		
0.55kW						0.55kW							
35	139	39.25	0.88	R 27 RF27	4	320	16	4.35	4.0	RX 57 RXF57	4		
38	131	36.79	0.94			367	14	3.79	4.6				
43	115	32.47	1.06			392	13	3.55	4.9				
48	102	28.78	1.20			443	12	3.14	5.3				
57	87	24.47	1.41			478	11	2.91	5.8				
62	79	22.32	1.54			527	10	2.64	6.6				
72	69	19.35	1.78			586	8.8	2.37	7.4	RX 37 RXF37	4		
77	64	18.08	1.90			681	7.6	2.04	8.6				
89	56	15.63	2.2			724	7.1	1.92	9.1				
105	47	13.28	2.6			842	6.1	1.65	11				
117	42	11.86	2.9			939	5.8	1.48	12				
137	36	10.13	3.2			1069	4.8	1.30	12				
148	33	9.41	3.4			R 17 RF17	4	426	12	3.26	1.24	RX 167R97 RF167R97	4
170	29	8.16	3.8					456	11	3.05	1.33		
182	27	7.63	3.9					527	10	2.64	1.53		
211	23	6.59	4.3					621	8.3	2.24	1.81		
248	20	5.60	4.7					695	7.4	2.00	2.03		
278	18	5.00	5.0					813	6.3	1.71	2.37		
326	15	4.27	5.4	869	5.9			1.60	2.53	R 147R77 RF147R77	4		
348	14	4.00	5.6	0.30	21596			4709	0.8				
412	12	3.37	6.2	0.33	19179			4182	0.88				
77	64	18.06	1.25	0.52	12185			2657	1.39			RX 137R77 RF137R77	4
89	55	15.57	1.44	0.60	10699			2333	1.58				
96	52	14.52	1.55	0.67	9562			2085	1.77				
110	45	12.69	1.77	0.95	6677			1456	2.5				
117	42	11.89	1.89	0.43	14804	3228	0.83	RX 107R77 RF107R77	4				
132	37	10.50	1.9	0.49	12992	2833	0.94						
149	33	9.31	2.0	0.54	11717	2555	1.04						
161	31	8.63	2.1	0.63	10140	2211	1.21						
176	28	7.91	2.2	0.71	8947	1951	1.37						
184	27	7.55	2.2	0.82	7819	1705	1.56						
197	25	7.04	2.3	0.90	7044	1536	1.73	RX 97R57 RF97R57	4				
226	22	6.15	2.4	1.0	6095	1329	2.0						
241	20	5.76	2.6	1.2	5347	1166	2.3						
273	18	5.09	2.7	0.67	9507	2073	0.79			RX 97R57 RF97R57	4		
308	16	4.51	2.8	0.7	8544	1863	0.88						
363	14	3.83	3.1	0.76	8434	1839	0.89						
171	30	5.18	2.3	0.87	7287	1589	1.03	RX 97R57 RF97R57	4				
195	26	4.53	2.9	0.9	7273	1586	1.03						
206	25	4.30	3.0	0.99	6407	1397	1.17						
235	22	3.77	3.7	1.0	6237	1360	1.21						
268	19	5.18	3.7	1.1	5632	1228	1.34						
307	17	4.53	4.6	1.2	5623	1226	1.34						
323	16	4.30	4.7	1.3	4999	1090	1.50	RX 97R57 RF97R57	4				
369	14	3.77	5.9	1.5	4361	951	1.72						
434	12	3.20	7.9	1.7	3811	831	1.97						
481	11	2.89	9.3	1.9	3348	730	2.2						
547	9.4	2.54	12	1.3	5022	1095	0.80			RX 97R57 RF97R57	4		
579	8.9	2.40	13	1.4	4783	1043	0.85						
681	7.6	2.04	17	1.5	4251	927	0.95						
747	6.9	1.86	17	1.6	4072	888	0.99						
863	6.0	1.61	18	1.7	3724	812	1.09						
203	25	4.35	2.5	1.8	3609	787	1.12	RX 97R57 RF97R57	4				
234	22	3.79	2.9	3.9	1637	357	2.5						
249	21	3.55	3.1	4.4	1435	313	2.8						
282	18	3.14	3.3	2.2	2894	631	0.97						
304	17	2.91	3.7	2.5	2568	560	1.10						
				2.9	2220	484	1.27						
				3.2	1972	430	1.43						
				3.7	1738	379	1.62						
				4.1	1541	336	1.83						
				4.7	1357	296	2.1						
				5.6	1142	249	2.5						



输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f_s	机 型 号 Type Type	极 数 Pole p	输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f_s	机 型 号 Type Type	极 数 Pole p
0.75kW						0.75kW					
3.5	1816	396	0.80	R 87R57 RF87R57	4	13	516	106.58	0.82	R 57 RF57	4
3.9	1656	361	0.91			14	479	98.99	0.88		
4.0	1610	351	1.04			15	435	89.71	0.97		
4.6	1399	305	1.19			17	390	80.55	1.08		
4.7	1376	300	1.35			20	335	69.23	1.26		
5.2	1224	267	1.70			21	314	64.85	1.35		
5.4	1174	256	2.0			24	277	57.29	1.52		
5.9	1078	235	2.4			26	258	53.22	1.64		
2.8	2445	245.50	1.65	R 107 RF107	8	29	234	48.23	1.81		
3.0	2259	226.11	1.81			32	210	43.30	2.0		
3.4	1995	200.87	2.0			37	181	37.30	2.3		
3.1	2138	215.94	1.32	R 97 RF97	8	40	170	35.07	2.5		
3.7	1841	185.97	1.53			46	146	30.18	2.9		
4.0	1674	169.06	1.68			52	131	26.97	3.2		
3.6	1901	256.89	1.49	R 97 RF97	6	53	130	26.31	3.3		
3.8	1782	240.83	1.58			56	124	24.99	3.4		
4.2	1598	215.94	1.76			63	108	21.93	3.9		
4.8	1403	289.60	2.0	R 97 RF97	4	75	92	18.60	4.6		
5.4	1244	256.89	2.3			20	332	68.54	0.85	R 47 RF47	4
5.8	1167	240.83	2.4			22	311	64.21	0.91		
6.4	1046	215.94	2.7			25	275	56.73	1.03		
7.5	901	185.97	3.1			26	255	52.69	1.10		
8.2	819	169.06	3.4			29	231	47.75	1.22		
4.2	1602	216.54	0.91	R 87 RF87	6	32	208	42.87	1.36		
4.4	1522	205.71	0.96			38	179	36.93	1.58		
5.0	1345	181.77	1.08			40	168	34.73	1.68		
5.9	1149	155.34	1.27			47	145	29.88	1.95		
6.4	1054	142.41	1.38			52	130	26.74	2.2		
5.6	1194	246.54	1.22	R 87 RF87	4	53	129	26.70	2.2		
6.4	1049	216.54	1.39			59	114	23.59	2.5		
6.8	996	205.71	1.46			60	113	23.28	2.5		
7.6	880	181.77	1.65			64	106	21.81	2.7		
8.9	752	155.34	1.94			72	93	19.27	3.0		
9.8	690	142.41	2.1			78	87	17.89	3.1		
11	605	124.97	2.4			86	79	16.22	3.3		
12	574	118.43	2.5			29	233	48.08	0.81	R 37 RF37	4
13	502	103.65	2.9			31	217	44.81	0.87		
15	452	93.38	3.2			35	190	39.17	0.99		
8.3	807	166.59	0.96	R 77 RF77	4	38	178	36.72	1.06		
9.5	706	145.67	1.09			43	157	32.40	1.20		
10	670	138.39	1.15			48	139	28.73	1.35		
11	588	121.42	1.31			57	118	24.42	1.59		
13	499	102.99	1.55			62	110	22.27	1.71		
15	450	92.97	1.71			72	96	19.31	1.97		
17	396	81.80	1.95			77	89	18.05	2.1		
18	375	77.24	2.1			89	77	15.60	2.4		
21	319	65.77	2.4			105	66	13.25	2.7		
25	273	56.38	2.8			117	59	11.83	2.9		
27	247	50.90	3.1			137	50	10.11	3.2		
31	217	44.78	3.6			147	47	9.47	3.4		
33	205	42.29	3.8			48	139	28.78	0.88	R 27 RF27	4
11	625	128.97	0.90	R 67 RF67	4	57	119	24.47	1.03		
12	552	113.94	1.02			62	110	22.32	1.11		
13	513	105.83	1.10			72	96	19.35	1.28		
14	465	95.91	1.21			77	89	18.08	1.37		
16	417	86.11	1.35			89	77	15.63	1.58		
19	359	74.17	1.57			105	66	13.28	1.86		
20	338	69.75	1.67			117	59	11.86	2.1		
23	297	61.26	1.90			137	50	10.13	2.3		
24	276	56.89	2.0			148	47	9.41	2.5		
27	250	51.56	2.3			170	40	8.16	2.7		
30	224	46.29	2.5			182	38	7.63	2.8		
						211	33	6.59	3.1		
						248	28	5.60	3.4		
						278	25	5.00	3.6		



输出转速	输出扭矩	传动比	使用系数	机 型 号	极 数	输出转速	输出扭矩	传动比	使用系数	机 型 号	极 数					
Output speed	Output torque	Ratio	Service factor	Type	Pole	Output speed	Output torque	Ratio	Service factor	Type	Pole					
r/min	Nm	i	f _B	Type	p	r/min	Nm	i	f _B	Type	p					
0.75kW						1.1kW										
77	89	18.06	0.89	R 17 RF17	4	0.53	17744	2657	0.95	R 167R97 RF167R97	4					
89	77	15.57	1.04			0.60	15580	2333	1.09							
96	72	14.52	1.11			0.67	13924	2085	1.22							
110	63	12.69	1.27			0.75	12535	1877	1.35							
117	59	11.89	1.36			0.84	11153	1670	1.52							
132	52	10.50	1.41			0.96	9723	1456	1.74							
149	46	9.31	1.47			1.1	8655	1296	2.0							
176	39	7.91	1.48			1.2	7593	1137	2.2							
184	37	7.55	1.57			0.63 0.72 0.82 0.91 1.1 1.2 1.4 1.6 1.8 2.0	14765 13029 11386 10258 8875 7787 6872 5937 5236 4641	2211 1951 1705 1536 1329 1166 1029 889 784 695	0.83 0.94 1.07 1.19 1.38 1.57 1.78 2.1 2.3 2.6	R 147R77 RF147R77	4 4					
197	35	7.04	1.67													
226	30	6.15	1.73													
241	28	5.76	1.75													
273	25	5.09	1.90													
308	22	4.51	2.0													
363	19	3.83	2.2													
201	35	4.53	2.2	RX 67 RXF67	6											
212	33	4.30	2.3													
241	29	3.77	2.8													
284	25	3.20	3.8													
268	26	5.18	2.7	RX 67 RXF67	4	1.0	9082	1360	0.83	R 137R77 RF137R77	4 4					
307	23	4.53	3.4			1.1	8201	1228	0.92							
323	22	4.30	3.5			1.2	8187	1226	0.92							
369	19	3.77	4.3			1.3	7279	1090	1.03							
434	16	3.20	5.8			1.3	7212	1080	1.04							
481	15	2.89	6.8			1.4	6812	1020	1.10							
547	13	2.54	8.6			1.5	6351	951	1.18							
579	12	2.40	9.5			1.6	5803	869	1.30							
681	10	2.04	12			1.7	5550	831	1.36							
747	9	1.86	13			1.9	4875	730	1.54							
863	8	1.61	13			2.2	4201	629	1.79							
240	29	3.79	2.2	RX 57 RXF57	6	2.6	3666	549	2.1	R 107R77 RF107R77	4 4					
256	27	3.55	2.4			2.9	3272	490	2.3							
290	24	3.14	2.5			2.0	4621	692	0.87							
313	22	2.91	2.8			2.3	3994	598	1.01							
345	20	2.64	3.2			2.6	3539	530	1.14							
320	22	4.35	2.9	RX 57 RXF57	4	2.9	3199	479	1.26			R 97R57 RF97R57	4 4			
367	19	3.79	3.4			3.4	2711	406	1.49							
392	18	3.55	3.6			3.9	2384	357	1.70							
443	16	3.14	3.9			4.5	2090	313	1.93							
478	15	2.91	4.3			5.1	1850	277	2.2							
527	13	2.64	4.9			5.7	1636	245	2.5							
586	12	2.37	5.4			3.3	2872	430	0.98	R 87R57 RF87R57	4 4					
681	11	2.04	6.3			3.7	2531	379	1.11							
724	10	1.92	6.7			4.2	2244	336	1.26							
842	9	1.65	7.8			4.7	1977	296	1.43							
939	8	1.48	8.6			5.6	1663	249	1.70							
1069	7	1.30	9.0			6.0	1563	234	1.80							
456	15	3.05	0.97	RX 37 RXF37	4	6.7	1396	209	2.0							
527	13	2.64	1.13			5.2	1783	267	0.82							
621	11	2.24	1.33			5.5	1710	256	0.85							
695	10	2.00	1.49			6.0	1569	235	0.93							
813	9	1.71	1.74			6.1	1543	231	0.94							
869	8	1.60	1.86			6.7	1389	208	1.05							
						7.2	1302	195	1.12							
						2.8	3586	245.50	1.13	R 107 RF107	8 8					
				3.0	3283	226.11	1.23									
				3.4	2901	200.87	1.39									
				4.0	2461	167.29	1.64									

R



输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f _s	机 型 号 Type Type	极 数 Pole p	输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f _s	机 型 号 Type Type	极 数 Pole p
1.1kW						1.1kW					
3.5	2788	256.89	1.02	R 97 RF97	6	20	488	69.23	0.87	R 57 RF57	4
3.8	2613	240.83	1.08		6	22	457	64.85	0.92		
4.2	2343	215.94	1.20		6	24	404	57.29	1.05		
4.9	2018	185.97	1.39		6	26	375	53.22	1.13		
5.4	1812	256.89	1.56	R 97 RF97	4	29	340	48.23	1.24		
5.8	1699	240.83	1.66			32	305	43.30	1.39		
6.5	1523	215.94	1.85			38	263	37.30	1.61		
7.5	1312	185.97	2.1			40	247	35.07	1.71		
8.3	1192	169.06	2.4			46	213	30.18	1.99		
9.3	1064	150.78	2.7			52	190	26.97	2.2		
11	894	126.75	3.2			53	186	26.31	2.3		
12	822	116.48	3.4	R 87 RF87	4	56	176	24.99	2.4		
6.5	1527	216.54	0.95			64	155	21.93	2.7		
6.8	1451	205.71	1.00			75	131	18.60	3.2		
7.7	1282	181.77	1.14			83	118	16.79	3.6		
9.0	1096	155.34	1.33			29	337	47.75	0.84	R 47 RF47	4
9.8	1004	142.41	1.45			33	302	42.87	0.93		
11	881	124.97	1.65			38	260	36.93	1.08		
12	835	118.43	1.74			40	245	34.73	1.15		
14	731	103.65	1.99			47	211	29.88	1.34		
15	659	93.38	2.2			52	188	26.70	1.50		
17	578	81.92	2.5			59	166	23.59	1.69		
19	510	72.37	2.9			60	164	23.28	1.72		
22	448	63.50	3.3			64	154	21.81	1.83		
23	424	60.18	3.4			73	136	19.27	2.0		
27	372	52.67	3.9			78	126	17.89	2.2		
12	856	121.42	0.90	R 77 RF77	4	86	114	16.22	2.3		
14	726	102.99	1.06			96	103	14.56	2.4		
15	656	92.97	1.18			112	88	12.54	2.7		
17	577	81.80	1.34			119	83	11.79	2.8		
18	545	77.24	1.41			138	72	10.15	3.0		
21	464	65.77	1.66			154	64	9.07	3.2		
25	398	56.38	1.94			43	229	32.40	0.82	R 37 RF37	4
28	359	50.90	2.1			49	203	28.73	0.93		
31	316	44.78	2.4			57	172	24.42	1.09		
33	298	42.29	2.6			73	139	19.31	1.35		
39	254	36.01	3.0			78	130	18.05	1.45		
43	231	32.72	3.3			90	112	15.60	1.67		
16	607	86.11	0.93	R 67 RF67	4	106	95	13.25	1.87		
19	523	74.17	1.08			118	85	11.83	2.0		
20	492	69.75	1.15			138	73	10.11	2.2		
23	432	61.26	1.31			148	68	9.47	2.3		
25	401	56.89	1.41			176	57	7.97	2.6		
27	364	51.56	1.55			210	48	6.67	2.8		
30	326	46.29	1.73			247	41	5.67	3.3		
35	281	39.88	1.9			277	36	5.06	3.5		
37	265	37.50	2.0			72	139	19.35	0.88	R 27 RF27	4
43	228	32.27	2.2			77	130	18.08	0.94		
49	203	28.83	2.4			90	113	15.63	1.09		
50	201	28.13	2.5			105	96	13.28	1.25		
52	192	26.72	2.6			118	85	11.86	1.42		
60	169	23.44	3.1			138	73	10.13	1.57		
70	143	19.89	3.9			172	59	8.16	1.86		
						183	55	7.63	1.92		
						212	47	6.59	2.1		
						250	40	5.60	2.3		
						280	36	5.00	2.5		
						328	31	4.27	2.7		
						350	29	4.00	2.8		
						415	24	3.37	3.1		



输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f _B	机 型 号 Type Type	极 数 Pole p	输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f _B	机 型 号 Type Type	极 数 Pole p
1.1kW						1.5kW					
249	41	5.63	2.5	RX 77	4	1.3	10038	1090	0.75		
262	39	5.35	2.5	RXF77	4	1.4	9393	1020	0.80		
296	35	4.73	3.3			1.5	8758	951	0.86		
						1.6	8003	869	0.94		
201	51	4.53	1.50	RX 67	6	1.7	7653	831	0.98		
212	49	4.30	1.55	RXF67	6	1.9	6723	730	1.12		
241	43	3.77	1.92			2.0	6299	684	1.19	R 137R77	4
						2.2	5792	629	1.30	RF137R77	4
309	33	4.53	2.3			2.4	5479	595	1.37		
326	32	4.30	2.4			2.6	5056	549	1.49		
371	28	3.77	2.9			2.9	4512	490	1.67		
438	24	3.20	4.0			3.3	3941	428	1.91		
484	21	2.89	4.7	RX 67	4	3.7	3444	374	2.2		
551	19	2.54	5.9	RXF67	4	4.4	2919	317	2.6		
583	18	2.40	6.6								
686	15	2.04	8.4			2.6	4827	530	0.84		
753	14	1.86	8.7			2.7	4644	510	0.87		
870	12	1.61	9.1			2.9	4362	479	0.93		
1000	10	1.40	9.5			3.0	4216	463	0.96	R 107R77	4
						3.4	3697	406	1.09	RF107R77	4
240	43	3.79	1.5	RX 57	6	3.9	3251	357	1.24		
256	40	3.55	1.6	RXF57	6	4.5	2850	313	1.42		
290	36	3.14	1.7								
313	33	2.91	1.9			4.2	3060	336	0.92		
345	30	2.64	2.2			4.7	2696	296	1.05		
						5.6	2268	249	1.24	R 97R57	4
369	28	3.79	2.3			6.0	2131	234	1.32	RF97R57	4
394	26	3.55	2.5			6.7	1903	209	1.48		
446	23	3.14	2.6								
481	21	2.91	2.9			3.1	4413	226.11	0.92		
530	19	2.64	3.3	RX 57	4	3.5	3920	200.87	1.03	R 107	8
591	17	2.37	3.7	RXF57	4	4.1	3265	167.29	1.24	RF107	8
686	15	2.04	4.3			4.4	3045	156.04	1.32		
729	14	1.92	4.6								
848	12	1.65	5.3			3.7	3593	245.50	1.12		
946	11	1.48	5.9			4.1	3309	226.11	1.22		
1077	10	1.30	6.2			4.6	2940	200.87	1.37	R 107	6
						5.5	2449	167.29	1.65	RF107	6
700	15	2.00	1.02	RX 37	4	5.8	2304	156.04	1.77		
819	13	1.71	1.19	RXF37	4	6.6	2041	139.47	1.98		
875	12	1.60	1.27								
1.5kW											
0.60	21246	2333	0.80			5.4	2417	256.89	1.14		
0.67	18987	2085	0.89			5.8	2316	240.83	1.22		
0.75	17093	1877	0.99			6.5	2077	215.94	1.36		
0.84	15208	1670	1.11	R 167R97	4	7.5	1789	185.97	1.58		
0.96	13259	1456	1.28	RF167R97	4	8.3	1626	169.06	1.73	R 97	4
1.1	11802	1296	1.43			9.3	1450	150.78	1.94	RF97	4
1.2	10354	1137	1.63			11	1219	126.75	2.3		
1.4	9213	1012	1.84			12	1120	116.48	2.5		
						14	995	103.44	2.8		
						15	889	92.47	3.2		
3.2	3934	432	3.1	R 147R87	4						
3.8	3388	373	3.6	RF147R87	4						
0.82	15527	1705	0.8			7.7	1748	181.77	0.83		
0.91	13988	1536	0.87			9.0	1494	155.34	0.98		
1.1	12103	1329	1.01			9.8	1370	142.41	1.06		
1.2	10618	1166	1.15			11	1202	124.97	1.21		
1.4	9371	1029	1.30	R 147R77	4	12	1139	118.43	1.28		
1.6	8096	889	1.51	RF147R77	4	14	997	103.65	1.46		
1.8	7140	784	1.71			15	898	93.38	1.62		
2.0	6329	695	1.93			17	788	81.92	1.85	R 87	4
2.3	5528	607	2.2			19	696	72.37	2.1	RF87	4
2.6	4981	547	2.5			22	611	63.50	2.4		
						23	579	60.18	2.5		
						27	507	52.67	2.9		
						30	456	47.45	3.2		
						34	400	41.63	3.6		
						38	353	36.73	4.1		



输出转速	输出扭矩	传动比	使用系数	机 型 号	极 数	输出转速	输出扭矩	传动比	使用系数	机 型 号	极 数				
Output speed	Output torque	Ratio	Service factor	Type	Pole	Output speed	Output torque	Ratio	Service factor	Type	Pole				
r/min	Nm	i	f _B	Type	p	r/min	Nm	i	f _B	Type	p				
1.5kW						1.5kW									
15	894	92.97	0.86	R 77 RF77	4	73	186	19.31	1.01	R 37 RF37	4				
17	787	81.80	0.98			78	174	18.05	1.08						
18	743	77.24	1.04			90	150	15.60	1.25						
21	633	65.77	1.22			106	127	13.25	1.40						
25	542	56.38	1.42			118	114	11.83	1.51						
28	490	50.90	1.57			138	97	10.11	1.64						
31	431	44.78	1.79			148	91	9.47	1.72						
33	407	42.29	1.90			176	77	7.97	1.91						
39	346	36.01	2.2			210	64	6.67	2.1						
43	315	32.72	2.4			247	55	5.67	2.4						
49	273	28.35	2.8			277	49	5.06	2.6						
57	237	24.67	3.1			324	42	4.32	2.9						
60	225	23.37	3.4			346	39	4.05	2.9						
65	206	21.43	3.7			411	33	3.41	3.2						
74	181	18.80	4.1												
23	589	61.26	0.96	R 67 RF67	4	90	150	15.63	0.81	R 27 RF27	4				
25	547	56.89	1.03			105	128	13.28	0.96						
27	496	51.56	1.14			118	114	11.86	1.06						
30	445	46.29	1.27			138	97	10.13	1.18						
35	384	39.88	1.47			172	78	8.16	1.39						
37	361	37.50	1.56			183	73	7.63	1.43						
43	310	32.27	1.82			212	63	6.59	1.57						
49	277	28.83	2.0			250	54	5.60	1.73						
50	276	28.13	2.0			280	48	5.00	1.86						
52	262	26.72	2.1			328	41	4.27	1.99						
60	230	23.44	2.4			350	38	4.00	2.1						
70	195	19.89	2.9			415	32	3.37	2.3						
78	176	17.95	3.2												
26	523	53.22	0.8			R 57 RF57	4	249	54			5.63	1.91	RX 77 RXF77	4
29	474	48.23	0.9					262	51			5.35	1.88		
32	425	43.30	1.0	296	45			4.73	2.5						
38	366	37.30	1.15	347	39			4.04	3.5						
40	344	35.07	1.23	378	36			3.70	4.0						
46	296	30.18	1.43	431	31			3.25	5.5						
52	265	26.97	1.60	455	30			3.08	6.1						
53	258	26.31	1.64	519	26			2.70	7.8						
56	245	24.99	1.72	576	23			2.43	8.6						
64	215	21.93	1.96	309	44			4.53	1.77						
75	183	18.60	2.3	326	41			4.30	1.82						
83	165	16.79	2.6	371	36			3.77	2.3						
95	145	14.77	2.8	438	31			3.20	3.1						
100	137	13.95	2.9	484	28			2.89	3.6						
118	117	11.88	3.3	551	24			2.54	4.5						
38	355	36.93	0.8	R 47 RF47	4	583	23	2.40	5.0	RX 67 RXF67	4				
40	334	34.73	0.84			686	20	2.04	6.4						
47	287	29.88	0.98			753	18	1.86	6.6						
52	257	26.70	1.1			870	15	1.61	6.9						
59	227	23.59	1.2			1000	13	1.40	7.3						
60	224	23.28	1.26			369	36	3.79	1.78						
64	210	21.81	1.34			394	34	3.55	1.90						
73	185	19.27	1.50			446	30	3.14	2.0						
78	172	17.89	1.58			481	28	2.91	2.3						
86	156	16.22	1.66			530	25	2.64	2.6						
96	140	14.56	1.8			591	23	2.37	2.8						
112	121	12.54	1.9			686	20	2.04	3.3						
119	113	11.79	2.0			729	18	1.92	3.5						
138	98	10.15	2.1			848	16	1.65	4.1						
154	87	9.07	2.2			946	14	1.48	4.5						
175	77	8.01	2.3	1077	13	1.30	4.7								
180	75	7.76	2.4												
201	67	6.96	2.5												
233	58	6.00	2.5												
248	54	5.64	2.7												
289	47	4.85	3.0												
323	42	4.34	3.3												
366	37	3.83	3.7												



输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f_B	机 型 号 Type Type	极 数 Pole p	输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f_B	机 型 号 Type Type	极 数 Pole p
2.2kW						2.2kW					
0.85	21991	1670	0.8	R 167R97 RF167R97	4	5.8	3414	245.50	1.18	R 107 RF107	4
0.98	19173	1456	0.88			6.3	3145	226.11	1.29		
1.1	17066	1296	1.0			7.1	2744	200.87	1.45		
1.2	14972	1137	1.1			8.5	2327	167.29	1.74		
1.4	13326	1012	1.27			9.1	2170	156.04	1.86		
1.6	11483	872	1.47			10	1940	139.47	2.1		
1.8	10140	770	1.67			11	1746	125.55	2.3		
2.1	8744	664	1.9			12	1581	113.70	2.6		
2.6	7111	540	1.72	R 147R87 RF147R87	4	14	1402	100.82	2.9	R 97 RF97	4
3.1	6084	462	2.0			16	1286	91.16	3.2		
3.3	5689	432	2.1			6.6	3003	215.94	0.94		
3.8	4912	373	2.5			7.6	2586	185.97	1.09		
4.3	4346	330	2.8			8.4	2351	169.06	1.20		
1.2	15354	1166	0.80	R 147R77 RF147R77	4	9.4	2097	150.78	1.34		
1.4	13550	1029	0.90			11	1763	126.75	1.60		
1.6	11707	889	1.04			12	1620	116.48	1.74		
1.8	10324	784	1.18			14	1439	103.44	1.96		
2.0	9152	695	1.34			15	1286	92.48	2.2		
2.3	7993	607	1.53			17	1156	83.15	2.4		
2.6	7203	547	1.70			20	1004	72.17	2.8		
3.0	6321	480	1.93			22	906	65.12	3.1		
1.9	9721	730	0.77	R 137R77 RF137R77	4	24	832	59.84	3.4		
2.1	9108	684	0.83			27	739	53.14	3.8		
2.3	8376	629	0.90			30	661	47.51	4.3		
2.4	7923	595	0.95			11	1738	124.97	0.84	R 87 RF87	4
2.6	7311	549	1.03			12	1647	118.43	0.88		
2.9	6525	490	1.15			14	1442	103.65	1.01		
3.3	5699	428	1.32			15	1299	93.38	1.12		
3.8	4980	374	1.51			17	1139	81.92	1.28		
4.5	4221	317	1.78			20	1007	72.37	1.45		
5.0	3808	286	1.97			22	883	63.50	1.65		
5.6	3377	250	2.2			24	837	60.18	1.74		
6.4	2958	219	2.5			27	733	52.67	1.99		
3.9	4822	357	0.84	R 107R77 RF107R77	4	30	660	47.45	2.2		
4.4	4336	321	0.93			34	579	41.63	2.5		
4.5	4228	313	0.96			39	511	36.73	2.9		
5.1	3741	277	1.08			41	478	34.34	3.0		
5.5	3458	256	1.17			44	453	32.57	3.2		
6.7	2809	208	1.44			45	434	31.22	3.4		
6.0	3125	234	0.90	R 97R57 RF97R57	4	51	387	27.81	3.8	R 77 RF77	4
6.7	2791	209	1.01			61	325	23.40	4.5		
3.2	6212	223.34	1.21	R 137 RF137	8	66	299	21.51	4.7		
3.8	5234	188.16	1.43			22	915	65.77	0.8		
4.1	4851	174.4	1.55			25	784	56.38	1.0		
4.5	4348	156.31	1.73			28	708	50.90	1.1		
5.0	3925	141.12	1.92			32	623	44.78	1.2		
5.5	3565	128.18	2.1			34	588	42.29	1.31		
6.2	3163	113.72	2.4			39	501	36.01	1.54		
6.9	2871	103.2	2.6			43	455	32.72	1.69		
4.7	4220	200.87	0.96	R 107 RF107	6	50	394	28.35	1.95		
5.6	3515	167.29	1.15			58	343	24.67	2.1		
6.0	3278	156.04	1.23			61	325	23.37	2.4		
6.7	2930	139.47	1.38			66	298	21.43	2.6		
						76	261	18.80	2.8		
						80	248	17.82	3.0		
						91	217	15.60	3.2		
						101	195	14.05	3.5		

R



输出转速	输出扭矩	传动比	使用系数	机 型 号	极 数	输出转速	输出扭矩	传动比	使用系数	机 型 号	极 数		
Output speed	Output torque	Ratio	Service factor	Type	Pole	Output speed	Output torque	Ratio	Service factor	Type	Pole		
r/min	Nm	i	f _B	Type	p	r/min	Nm	i	f _B	Type	p		
2.2kW						2.2kW							
36	555	39.88	0.98	R 67 RF67	4 4	300	69	4.73	1.69	RX 77 RXF77	4 4		
38	522	37.50	1.03			351	59	4.04	2.3				
44	449	32.27	1.13			384	54	3.70	2.7				
49	401	28.83	1.22			437	47	3.25	3.6				
61	326	23.44	1.61			461	45	3.08	4.1				
71	277	19.89	2.0			526	39	2.70	5.2				
79	250	17.95	2.2			584	35	2.43	5.7				
90	220	15.79	2.4			667	31	2.13	6.1				
95	207	14.91	2.5			755	27	1.88	6.4				
112	177	12.70	2.8			850	24	1.67	6.7				
123	160	11.54	2.9			1000	21	1.42	7.1				
142	139	10.00	3.2										
163	121	8.70	3.3										
182	108	7.79	3.4										
38	519	37.30	0.82	R 57 RF57	4 4	377	55	3.77	1.50	RX 67 RXF67	4 4		
40	488	35.07	0.87			444	46	3.20	2.0				
47	420	30.18	1.01			491	42	2.89	2.4				
53	375	26.97	1.13			559	37	2.54	3.0				
65	305	21.93	1.39			592	35	2.40	3.3				
76	259	18.60	1.64			696	30	2.04	4.3				
85	234	16.79	1.81			763	27	1.86	4.4				
96	205	14.77	1.99			882	23	1.61	4.6				
102	194	13.95	2.1			1014	20	1.40	4.8				
120	165	11.88	2.3										
132	150	10.79	2.4			452	46	3.14	1.34			RX 57 RXF57	4 4
152	130	9.35	2.7			538	38	2.64	1.69				
157	126	9.06	2.8			599	34	2.37	1.89				
178	111	7.97	3.0			696	30	2.04	2.2				
				740	28	1.92	2.3						
				861	24	1.65	2.7						
				959	21	1.48	3.0						
				1092	19	1.30	3.1						
74	268	19.27	1.03	R 47 RF47	4 4	3.0kW							
88	226	16.22	1.15			1.2	20417	1137	0.83	R 167R97 RF167R97	4 4		
98	203	14.56	1.23			1.4	18172	1012	0.93				
113	174	12.54	1.35			1.6	15658	872	1.08				
120	164	11.79	1.40			1.8	13827	770	1.22				
140	141	10.15	1.53			2.1	11923	664	1.42				
157	126	9.07	1.64			2.8	9158	510	1.85				
177	111	8.01	1.73										
183	108	7.76	1.42			2.6	9697	540	1.26	R 147R87 RF147R87	4 4		
204	97	6.96	1.54			3.1	8296	462	1.47				
237	83	6.00	1.76			3.3	7757	432	1.58				
252	78	5.64	1.86			3.8	6698	373	1.82				
293	67	4.85	2.1			4.3	5926	330	2.1				
327	60	4.34	2.3			5.0	5082	283	2.4				
371	53	3.83	2.5										
91	217	15.60	0.87	R 37 RF37	4 4	1.6	15963	889	0.8	R 147R77 RF147R77	4 4		
107	184	13.25	0.97			1.8	14078	784	0.87				
120	165	11.83	1.05			2.0	12480	695	0.98				
140	141	10.11	1.14			2.3	10900	607	1.12				
150	132	9.47	1.19			2.6	9822	547	1.24				
178	111	7.97	1.32										
213	93	6.67	1.46			2.7	9388	517	0.80			R 137R77 RF137R77	4 4
250	79	5.67	1.69			2.9	8898	490	0.85				
281	70	5.06	1.80			3.1	8226	453	0.91				
329	60	4.32	2.0			3.3	7772	428	0.97				
351	56	4.05	2.0			3.8	6791	374	1.11				
416	47	3.41	2.2			4.5	5756	317	1.31				
						5.0	5193	286	1.45				
						5.7	4540	250	1.66				
				6.5	3977	219	1.89						
140	141	10.13	0.81	R 27 RF27	4 4	5.6	4798	253	0.84	R 107R77 RF107R77	4 4		
215	92	6.59	1.09			5.8	4647	245	0.87				
254	78	5.60	1.19			6.8	3945	208	1.02				
284	70	5.00	1.28			7.8	3433	181	1.18				
333	59	4.27	1.38										
355	56	4.00	1.44										
421	47	3.37	1.58										



输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f_B	机 型 号 Type Type	极 数 Pole p	输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f_B	机 型 号 Type Type	极 数 Pole p
3.0kW						3.0kW					
3.2	8472	223.34	0.89	R 137 RF137	8	32	849	44.78	0.91	R 77 RF77	4
3.8	7137	188.16	1.05			34	802	42.29	0.96		
4.1	6615	174.40	1.14			39	683	36.01	1.13		
4.5	5929	156.31	1.27			43	621	32.72	1.24		
5.0	5353	141.12	1.40			50	538	28.35	1.43		
5.5	4862	128.18	1.55			58	468	24.67	1.57		
6.2	4314	113.72	1.74			61	443	23.37	1.74		
6.9	3914	103.20	1.92			66	406	21.43	1.90		
8.0	3364	88.70	2.20	R 137 RF137	6	76	357	18.80	2.1	R 67 RF67	4
4.3	6245	222.60	1.20			80	338	17.82	2.2		
5.1	5287	188.45	1.42			91	296	15.60	2.4		
5.5	4892	174.40	1.54			101	266	14.05	2.5		
6.1	4385	156.31	1.71			115	234	12.33	2.8		
6.8	3959	141.12	1.90			131	206	10.88	3.0		
7.5	3596	128.18	2.10			147	183	9.64	3.2		
8.4	3190	113.72	2.40			169	160	8.42	3.7		
9.3	2895	103.20	2.60			187	144	7.59	4.0		
6.2	4377	156.04	0.92	R 107 RF107	6	213	126	6.66	4.3	R 57 RF57	4
6.9	3913	139.47	1.03			61	445	23.44	1.18		
7.6	3522	125.55	1.15			71	377	19.89	1.50		
6.3	4288	226.11	0.94			79	340	17.95	1.63		
7.1	3810	200.87	1.06			90	299	15.79	1.76		
8.5	3172	167.29	1.27			95	283	14.91	1.8		
9.1	2959	156.04	1.37			112	241	12.70	2.0		
10	2645	139.47	1.53			123	219	11.54	2.1		
11	2381	125.55	1.70	R 107 RF107	4	142	190	10.00	2.3	R 47 RF47	4
12	2156	113.70	1.87			53	511	26.97	0.8		
14	1912	100.82	2.1			65	416	21.93	1.02		
16	1729	91.16	2.3			76	353	18.60	1.20		
18	1465	77.26	2.8			85	318	16.79	1.33		
20	1366	72.00	3.0			96	280	14.77	1.46		
9.4	2860	150.78	0.99			102	265	13.95	1.53		
11	2404	126.75	1.17			120	225	11.88	1.69		
12	2209	116.48	1.28	R 97 RF97	4	132	205	10.79	1.79	R 37 RF37	4
14	1962	103.44	1.44			152	177	9.35	2.0		
15	1754	92.48	1.61			157	172	9.06	2.1		
17	1577	83.15	1.79			178	151	7.97	2.2		
20	1369	72.17	2.1			189	143	7.53	2.3		
22	1235	65.12	2.3			222	122	6.41	2.6		
24	1135	59.84	2.5			244	110	5.82	2.7		
27	1008	53.14	2.8			281	96	5.05	3.0		
30	901	47.51	3.1	R 87 RF87	4	323	83	4.39	3.2		
33	810	42.72	3.5			88	308	16.22	0.84	R 37 RF37	4
38	703	37.08	4.0			98	276	14.56	0.90		
43	630	33.20	4.3			113	238	12.54	0.99		
15	1771	93.38	0.82			120	224	11.79	1.03		
17	1554	81.92	0.94			140	192	10.15	1.12		
20	1373	72.37	1.06			157	172	9.07	1.20		
22	1204	63.50	1.21			177	152	8.01	1.27		
24	1141	60.18	1.28			183	147	7.76	1.04		
27	999	52.67	1.46	R 87 RF87	4	204	132	6.96	1.13	R 37 RF37	4
30	900	47.45	1.62			237	114	6.00	1.29		
34	790	41.63	1.85			252	107	5.64	1.36		
39	697	36.73	2.1			293	92	4.85	1.53		
41	651	34.34	2.2			327	82	4.34	1.67		
44	618	32.57	2.4			371	73	3.83	1.86		
45	592	31.22	2.5			140	192	10.11	0.83		
51	528	27.84	2.8			150	180	9.47	0.87		
53	527	27.81	2.8	R 87 RF87	4	178	151	7.97	0.97	R 37 RF37	4
61	444	23.40	3.3			213	126	6.67	1.07		
66	408	21.51	3.5			250	108	5.67	1.24		
74	362	19.10	3.6			281	96	5.06	1.32		
83	324	17.08	4.0			329	82	4.32	1.45		
93	291	15.35	4.3			351	77	4.05	1.49		
						416	65	3.41	1.63		



R

输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f _s	机 型 号 Type Type	极 数 Pole p	输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f _s	机 型 号 Type Type	极 数 Pole p
3.0kW						4.0kW					
254	106	5.60	0.88	R 27 RF27	4	3.8	8877	376	0.85	R 137R77 RF137R77	4
284	95	5.00	0.94		4	3.9	8830	374	0.85		
333	81	4.27	1.01			4.2	8004	339	0.94		
355	76	4.00	1.05			4.5	7484	317	1.00		
421	64	3.37	1.2			4.8	7012	297	1.07		
						5.0	6752	286	1.11		
						5.8	5902	250	1.27		
						6.6	5171	219	1.45		
109	258	6.47	4.31	RX 127 RXF127	8						
						7.5	4509	191	0.90	R 107R77 RF107R77	4
220	127	6.44	1.42	RX 87 RXF87	4	8.0	4273	181	0.95	R 147 RF147	8
256	110	5.55	1.92		4	8.6	3943	167	1.03		
281	100	5.05	2.3								
316	89	4.50	3.1			4.4	8152	163.46	1.50		
376	75	3.78	3.8			4.9	7324	146.85	1.67		
						6.0	5946	119.24	2.0		
						6.5	5487	110.03	2.2		
300	94	4.73	1.24	RX 77 RXF77	4					R 137 RF137	8
351	80	4.04	1.68		4	4.1	8698	174.40	0.86		
384	73	3.70	1.97			4.6	7796	156.31	0.96		
437	64	3.25	2.7			5.1	7038	141.12	1.07		
461	61	3.08	3.0			5.6	6393	128.18	1.18		
						6.3	5671	113.72	1.33		
						7.0	5147	103.20	1.46		
377	75	3.77	1.10	RX 67 RXF67	4					R 137 RF137	6
444	63	3.20	1.49		4	4.3	8354	223.34	0.90		
491	57	2.89	1.74			5.1	7038	188.16	1.07		
559	50	2.54	2.2			5.5	6523	174.40	1.15		
592	47	2.40	2.4			6.1	5847	156.31	1.29		
696	40	2.04	3.1			6.8	5278	141.12	1.42		
763	37	1.86	3.2			7.5	4794	128.18	1.57		
882	32	1.61	3.4			8.4	4254	113.72	1.77		
1014	28	1.40	3.5			9.3	3860	103.2	1.95		
						11	3318	88.70	2.3		
452	62	3.14	0.98	RX 57 RXF57	4					R 107 RF107	4
538	52	2.64	1.24		4	9	4172	167.29	0.97		
599	47	2.37	1.38			10	3891	156.04	1.04		
696	40	2.04	1.61			11	3478	139.47	1.16		
740	38	1.92	1.71			12	3131	125.55	1.29		
861	33	1.65	1.99			13	2835	113.70	1.43		
959	29	1.48	2.2			14	2514	100.82	1.61		
1092	26	1.30	2.3			16	2273	91.16	1.78		
						19	1927	77.26	2.1		
						20	1795	72.00	2.3		
						22	1616	64.81	2.5		
						25	1464	58.69	2.8		
						28	1298	52.05	3.1		
4.0kW											
1.7	20588	872	0.82	R 167R97 RF167R97	4	12	2905	116.48	0.97	R 97 RF97	4
1.9	18179	770	0.93		4	14	2579	103.44	1.09		
2.2	15677	664	1.08			16	2306	92.48	1.22		
2.8	12041	510	1.41			17	2073	83.15	1.36		
3.8	8972	380	1.89			20	1800	72.17	1.57		
4.3	7980	338	2.1			22	1624	65.12	1.74		
						24	1492	59.84	1.89		
2.7	12749	540	0.96	R 147R87 RF147R87	4	27	1325	53.14	2.1		
3.1	10908	462	1.12		4	30	1185	47.51	2.4		
3.3	10199	432	1.20			34	1065	42.72	2.6		
3.9	8806	373	1.39			39	925	37.08	3.0		
4.4	7791	330	1.57			43	828	33.20	3.2		
5.1	6682	283	1.83			45	803	32.22	3.3		
5.8	5902	250	2.1			54	669	26.84	3.6		
6.7	5100	216	2.4			58	624	25.03	4.3		
7.5	4509	191	2.7			64	558	22.37	4.6		
8.9	3801	161	3.2			71	502	20.14	4.9		
						78	455	18.24	6.2		
2.4	14331	607	0.85	R 147R77 RF147R77	4						
2.6	12915	547	0.95		4						
3.0	11333	480	1.08								
3.5	9609	407	1.27								



输出转速	输出扭矩	传动比	使用系数	机 型 号	极 数	输出转速	输出扭矩	传动比	使用系数	机 型 号	极 数		
Output speed	Output torque	Ratio	Service factor	Type	Pole	Output speed	Output torque	Ratio	Service factor	Type	Pole		
r/min	Nm	i	f _B	Type	p	r/min	Nm	i	f _B	Type	p		
4.0kW						4.0kW							
23	1583	63.5	0.92	R 87 RF87	4	142	253	10.15	0.85	R 47 RF47	4		
24	1501	60.18	0.97			159	226	9.07	0.86				
27	1313	52.67	1.11			180	200	8.01	0.91				
30	1183	47.45	1.23			207	174	6.96	0.96				
35	1038	41.63	1.40			240	150	6.00	0.98				
39	916	36.73	1.59			255	141	5.64	1.04				
42	856	34.34	1.70			297	121	4.85	1.17				
44	812	32.57	1.79			332	108	4.34	1.27				
46	779	31.22	1.87			376	96	3.83	1.42				
52	694	27.84	2.1										
53	693	27.81	2.2			109	344	6.47	3.23	RX 127	8		
62	584	23.40	2.5			121	310	5.88	3.59	RXF127	8		
67	536	21.51	2.7										
75	476	19.10	3.1			147	254	6.47	4.37	RX 127 RXF127	6 6		
84	426	17.08	3.1										
94	383	15.35	3.3			259	144	5.55	1.46	RX 87 RXF87	4		
108	332	13.33	3.6	285	131	5.05	1.78						
121	297	11.93	3.9	320	117	4.50	2.3						
				381	98	3.78	2.9						
40	898	36.01	0.86	R 77 RF77	4	356	105	4.04	1.28	RX 77 RXF77	4		
44	816	32.72	0.94			389	96	3.70	1.50				
51	707	28.35	1.09			443	84	3.25	2.0				
58	615	24.67	1.19			468	80	3.08	2.3				
62	583	23.37	1.32			533	70	2.70	2.9				
67	534	21.43	1.44			593	63	2.43	3.2				
77	469	18.80	1.56			676	55	2.13	3.4				
81	444	17.82	1.65			766	49	1.88	3.6				
92	389	15.60	1.79			862	43	1.67	3.7	RX 67 RXF67	4		
102	350	14.05	1.93			1014	37	1.42	3.9				
117	307	12.33	2.1			450	83	3.20	1.13				
132	271	10.88	2.3			498	75	2.89	1.33				
149	240	9.64	2.5			567	66	2.54	1.68				
171	210	8.42	2.8			600	62	2.40	1.85				
190	189	7.59	3.0			706	53	2.04	2.4	RX 57 RXF57	4		
216	166	6.66	3.3			774	48	1.86	2.4				
245	147	5.88	3.5			894	42	1.61	2.6				
276	130	5.21	3.7			1029	36	1.40	2.7				
72	496	19.89	1.14	R 67 RF67	4	545	69	2.64	0.95	RX 57 RXF57	4		
80	448	17.95	1.24			608	62	2.37	1.05				
91	394	15.79	1.34			706	53	2.04	1.22				
97	372	14.91	1.39			750	50	1.92	1.30				
113	317	12.70	1.54			873	43	1.65	1.51				
125	288	11.54	1.63			973	38	1.48	1.66				
144	249	10.00	1.77			1108	34	1.30	1.75				
166	217	8.70	1.91										
185	194	7.79	1.84										
196	184	7.36	1.90										
230	156	6.27	2.0										
253	142	5.70	2.1										
292	123	4.93	2.2										
336	107	4.29	2.4										
77	464	18.60	0.91	R 57 RF57	4	5.5kW							
86	419	16.79	1.01			2.2	21556	664	0.80	R 167R97 RF167R97	4		
97	368	14.77	1.11			2.5	18764	578	0.90				
103	348	13.95	1.16			2.8	16556	510	1.02				
121	296	11.88	1.29			3.3	14219	438	1.19				
133	269	10.79	1.36			3.8	12336	380	1.37				
154	233	9.35	1.49			4.3	10973	338	1.54				
159	226	9.06	1.56			4.7	9966	307	1.70				
181	199	7.97	1.68			5.1	9155	282	1.85				
191	188	7.53	1.75										
225	160	6.41	1.97			3.1	14998	462	0.81	R 147R87 RF147R87	4		
247	145	5.82	2.1			3.3	14024	432	0.87				
285	126	5.05	2.3			3.9	12109	373	1.01				
328	109	4.39	2.4			4.4	10713	330	1.14				
						5.1	9187	283	1.33				
						5.8	8116	250	1.51				
						6.7	7012	216	1.74				
				7.5	6201	191	1.97						



R

输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f _s	机 型 号 Type Type	极 数 Pole p	输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f _s	机 型 号 Type Type	极 数 Pole p
5.5kW						5.5kW					
3.7	12752	196.41	1.32	R 167 RF167	8	45	1105	32.22	2.2	R 97 RF97	4
4.5	10440	160.80	1.63		8	54	920	26.84	2.6		4
5.5	8469	130.44	1.99			58	858	25.03	3.1		
6.0	7855	120.99	2.17			64	767	22.37	3.3		
6.9	6779	104.41	2.50			71	691	20.14	3.6		
						79	625	18.24	3.8		
4.4	10613	163.46	1.15	R 147 RF147	8	89	554	16.17	4.1		
4.9	9534	146.85	1.28		8						
6.0	7742	119.24	1.57			30	1627	47.45	0.90	R 87 RF87	4
6.6	7144	110.03	1.72			35	1427	41.63	1.02		
						39	1259	36.73	1.16		
5.9	7960	163.46	1.54	R 147 RF147	6	44	1117	32.57	1.30		
6.5	7151	146.85	1.71		6	52	955	27.84	1.53		
8.0	6133	119.24	2.0			53	954	27.81	1.53		
8.8	5659	110.03	2.2			62	802	23.40	1.82		
10	4865	94.60	2.5			67	738	21.51	2.0		
12	4293	83.47	2.8			75	655	19.10	2.1		
5.6	8790	128.18	0.86	R 137 RF137	8	84	586	17.08	2.2		
6.3	7798	113.72	0.96		8	94	526	15.35	2.4		
7.0	7077	103.2	1.06			108	457	13.33	2.6		
8.1	6083	88.70	1.24			121	409	11.93	2.8		
						145	339	9.90	3.3		
5.5	8970	174.40	0.84	R 137 RF137	6	156	317	9.25	3.6		
6.1	8039	156.31	0.94		6	173	285	8.32	3.8		
6.8	7258	141.12	1.04			199	248	7.22	4.1		
7.5	6592	128.18	1.14								
8.4	5849	113.72	1.29			77	645	18.80	1.14	R 77 RF77	4
9.3	5308	103.20	1.42			81	611	17.82	1.20		
						92	535	15.60	1.30		
6.4	7658	223.34	0.98	R 137 RF137	4	102	482	14.05	1.40		
7.7	6451	188.16	1.17		4	117	423	12.33	1.53		
8.3	5980	174.40	1.26			132	373	10.88	1.66		
9.2	5359	156.31	1.40			149	331	9.64	1.79		
10	4839	141.12	1.55			171	289	8.42	2.1		
11	4395	128.18	1.71			190	260	7.59	2.2		
13	3899	113.72	1.93			216	228	6.66	2.4		
14	3538	103.20	2.1			245	202	5.88	2.52		
16	3041	88.70	2.5			276	179	5.21	2.68		
18	2774	80.91	2.7							R 67 RF67	4
20	2520	73.49	3.0			91	541	15.79	0.97		
22	2236	65.20	3.4			97	511	14.91	1.01		
24	2029	59.17	3.7			113	435	12.70	1.12		
28	1744	50.86	4.3			125	396	11.54	1.19		
						144	343	10.00	1.29		
11	4305	125.55	0.94	R 107 RF107	4	166	298	8.70	1.34		
13	3898	113.70	1.04		4	185	267	7.79	1.38		
14	3457	100.82	1.17			196	252	7.36	1.39		
16	3126	91.16	1.29			230	215	6.27	1.44		
19	2649	77.26	1.54			253	195	5.70	1.49		
20	2469	72.00	1.64			292	169	4.93	1.61		
22	2222	64.84	1.82			336	147	4.29	1.73		
25	2012	58.69	2.01							R 57 RF57	4
28	1785	52.05	2.3			97	506	14.77	0.81		
31	1614	47.06	2.5			103	478	13.95	0.85		
36	1367	39.88	3.0			121	407	11.88	0.93		
						133	370	10.79	0.99		
17	2851	83.15	0.99	R 97 RF97	4	154	321	9.35	1.08		
20	2475	72.17	1.14		4	181	273	7.97	1.22		
22	2233	65.12	1.26			191	258	7.53	1.27		
24	2052	59.84	1.37			225	220	6.41	1.43		
27	1822	53.14	1.55			247	200	5.82	1.51		
30	1629	47.51	1.73			285	173	5.05	1.66		
34	1465	42.72	1.93			328	151	4.39	1.75		
39	1271	37.08	2.2							R 47 RF47	4
43	1138	33.20	2.4			297	166	4.85	0.85		
52	944	27.54	2.7			332	149	4.34	0.92		
						376	131	3.83	1.03		



输出转速	输出扭矩	传动比	使用系数	机 型 号	极 数	输出转速	输出扭矩	传动比	使用系数	机 型 号	极 数		
Output speed	Output torque	Ratio	Service factor	Type	Pole	Output speed	Output torque	Ratio	Service factor	Type	Pole		
r/min	Nm	i	f _B	Type	p	r/min	Nm	i	f _B	Type	p		
5.5kW						7.5kW							
116	443	6.22	3.79	RX 157 RXF157	8 8	4.4	14408	330	0.85	R 147R87 RF147R87	4 4		
123	420	5.88	2.64	RX 127 RXF127	8 8	5.2	12356	283	0.99				
						5.8	10915	250	1.12				
						6.8	9431	216	1.30				
						7.6	8339	191	1.47				
147	350	6.47	3.18	RX 127 RXF127	6 6	9.1	7030	161	1.74				
164	315	5.88	3.53					3.7	18366	196.41	0.92	R 167 RF167	4 4
182	283	5.28	3.92					4.5	15036	160.80	1.13		
						5.5	12197	130.44	1.39				
						6.0	11314	120.99	1.50				
217	238	6.65	1.82	RX 107 RXF107	4 4	6.9	9763	104.41	1.73				
257	200	5.60	2.14										
277	186	5.19	3.52										
310	166	4.65	3.93										
247	208	5.82	1.9	RX 97 RXF97	4 4	4.9	13775	196.41	1.23	R 167 RF167	6 6		
297	173	4.85	2.1			6.0	11277	160.80	1.50				
319	162	4.52	3.5			7.4	9145	130.44	1.84				
356	144	4.04	3.9			7.9	8485	120.99	1.99				
396	130	3.64	4.3			9.2	7323	104.41	2.31				
436	118	3.30	4.7			10	6462	92.14	2.6				
493	104	2.92	5.4			12	5602	79.88	3.0				
545	94	2.64	5.9			14	4984	71.07	3.4				
643	80	2.24	7.0			15	4487	63.98	3.8				
735	70	1.96	7.6			16	4103	58.51	4.1				
878	59	1.64	8.1			4.4	15285	163.46	0.80	R 147 RF147	8 8		
1014	51	1.42	8.4			4.9	13732	146.85	0.89				
						6.0	11150	119.24	1.09				
						6.6	10289	110.03	1.20				
320	161	4.50	1.7	RX 87 RXF87	4 4	5.9	11464	163.46	1.07	R 147 RF147	6 6		
381	135	3.78	2.1			6.5	10299	146.85	1.19				
414	124	3.48	3.1			8.0	8363	119.24	1.45				
466	110	3.09	3.4			8.8	7717	110.03	1.59				
522	99	2.76	3.9			10	6635	94.60	1.84				
581	89	2.48	4.3			12	5854	83.47	2.1				
670	77	2.15	4.7										
443	116	3.25	1.47	RX 77 RXF77	4 4	7.7	8677	188.16	0.87	R 137 RF137	4 4		
468	110	3.08	1.65			8.4	8042	174.40	0.94				
533	97	2.70	2.1			9.3	7208	156.31	1.04				
593	87	2.43	2.3			10	6508	141.12	1.16				
676	76	2.13	2.5			11	5911	128.18	1.27				
766	67	1.88	2.6			13	5244	113.72	1.43				
862	60	1.67	2.7			14	4759	103.20	1.58				
1014	51	1.42	2.9			16	4090	88.70	1.84				
567	91	2.54	1.22	RX 67 RXF67	4 4	18	3731	80.91	2.0				
600	86	2.40	1.35			20	3389	73.49	2.2				
706	73	2.04	1.73			22	3007	65.20	2.5				
774	66	1.86	1.78			25	2729	59.17	2.8				
894	58	1.61	1.86			29	2345	50.86	3.2				
1029	50	1.40	2.0										
706	73	2.04	0.89	RX 57 RXF57	4 4	16	4204	91.16	0.96	R 107 RF107	4 4		
750	69	1.92	0.95			19	3563	77.26	1.13				
873	59	1.65	1.10			20	3320	72.00	1.22				
973	53	1.48	1.21			23	2989	64.81	1.35				
1108	46	1.30	1.27			25	2706	58.69	1.49				
						28	2400	52.05	1.68				
7.5kW						31	2170	47.06	1.86				
2.9	22268	510	0.80	R 167R97 RF167R97	4 4	37	1839	39.88	2.2				
3.3	19124	438	0.88			42	1607	34.84	2.5				
3.8	16591	380	1.02			48	1404	30.44	2.9				
4.3	14758	338	1.15			50	1344	29.14	3.0				
4.8	13404	307	1.26			54	1257	27.25	3.2				
5.2	12313	282	1.37			59	1134	24.60	3.6				
						65	1030	22.34	3.9				



输出转速	输出扭矩	传动比	使用系数	机 型 号	极 数	输出转速	输出扭矩	传动比	使用系数	机 型 号	极 数		
Output speed	Output torque	Ratio	Service factor	Type	Pole	Output speed	Output torque	Ratio	Service factor	Type	Pole		
r/min	Nm	i	f _s	Type	p	r/min	Nm	i	f _s	Type	p		
7.5kW						7.5kW							
24	2760	59.84	1.02	R 97 RF97	4 4	123	572	5.88	2.94	RX 127	6		
27	2451	53.14	1.15			136	515	5.28	3.26	RXF127	6		
31	2191	47.51	1.29			167	420	4.29	4.0				
34	1970	42.72	1.43										
39	1710	37.08	1.65					221	318	6.47	3.49	RX 127	4
44	1531	33.20	1.72					245	286	5.88	3.88	RXF127	4
45	1486	32.22	1.77										
53	1270	27.54	1.94					220	320	6.65	1.35	RX 107 RXF107	4 4
54	1238	26.84	1.98					260	269	5.60	1.59		
58	1154	25.03	2.30					281	250	5.19	2.6		
65	1032	22.37	2.48					314	224	4.65	2.9		
72	929	20.14	2.64			348	202	4.20	3.9				
80	841	18.24	2.79										
40	1694	36.73	0.86	R 87 RF87	4 4	251	280	5.82	1.41	RX 97 RXF97	4 4		
45	1502	32.57	0.97			301	233	4.85	1.59				
52	1284	27.84	1.13			323	217	4.52	2.6				
53	1282	27.81	1.1			361	194	4.04	2.9				
62	1079	23.40	1.35			401	175	3.64	3.2				
68	992	21.51	1.42			442	159	3.30	3.5				
76	881	19.10	1.54			500	140	2.92	4.0				
85	788	17.08	1.66										
95	708	15.35	1.78			324	216	4.50	1.26	RX 87 RXF87	4 4		
110	615	13.33	1.96			386	182	3.78	1.58				
122	550	11.93	2.1			420	167	3.48	2.3				
147	457	9.90	2.4			472	149	3.09	2.6				
158	427	9.25	2.7			529	133	2.76	2.9				
175	384	8.32	2.8			589	119	2.48	3.2				
202	333	7.22	3.0			679	103	2.15	3.5				
226	298	6.47	3.2			756	93	1.93	3.6				
272	247	5.36	3.5			913	77	1.60	3.8				
				1050	67	1.39	4.1						
78	867	18.80	0.85	R 77 RF77	4 4	449	156	3.25	1.09	RX 77 RXF77	4 4		
82	822	17.82	0.89			474	148	3.08	1.23				
94	719	15.60	0.97			541	130	2.70	1.56				
104	648	14.05	1.04			601	117	2.43	1.73				
118	569	12.33	1.14			685	102	2.13	1.84				
134	502	10.88	1.24			777	90	1.88	1.94				
151	445	9.64	1.33			874	80	1.67	2.0				
173	388	8.42	1.53			1028	68	1.42	2.1				
192	350	7.59	1.64										
219	307	6.66	1.78			575	122	2.54	0.91	RX 67 RXF67	4 4		
248	271	5.88	1.87			608	115	2.40	1.00				
280	240	5.21	2.00			716	98	2.04	1.28				
						785	89	1.86	1.32				
				907	77	1.61	1.38						
115	586	12.70	0.83	R 67 RF67	4 4	1043	67	1.40	1.45				
127	532	11.54	0.88			11kW							
146	461	10.00	0.96			4.9	18891	295	0.90	R 167R107 RF167R107	4 4		
168	401	8.70	0.99			5.1	18379	287	0.92				
187	359	7.79	1.02			5.2	17994	281	0.94				
198	339	7.36	1.03			6.1	15241	238	1.11				
233	289	6.27	1.07			7.0	13320	208	1.27				
256	263	5.70	1.11			8.3	11271	176	1.50				
296	227	4.93	1.20										
340	198	4.29	1.28										
183	368	7.97	0.91	R 57 RF57	4 4	4.3	21645	338	0.80	R 167R97 RF167R97	4 4		
194	347	7.53	0.95			4.8	19659	307	0.86				
228	296	6.41	1.07			5.2	18059	282	0.94				
251	268	5.82	1.12			5.8	16009	250	0.80	R 147R87 RF147R87	4 4		
289	233	5.05	1.23			6.8	13832	216	0.88				
333	202	4.39	1.30			7.6	12231	191	1.00				
123	572	5.88	1.94	9.1	10310	161	1.19						
156	449	6.22	3.74	RX 157 RXF157	6 6	9.2	10182	159	1.20				



输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f _B	机 型 号 Type Type	极 数 Pole p	输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f _B	机 型 号 Type Type	极 数 Pole p
11kW						11kW					
6.0	16540	160.80	1.02	R 167 RF167	6	135	732	10.83	2.7	R 97 RF97	4
7.4	13417	130.44	1.26		6	158	626	9.26	3.0		4
7.9	12445	120.99	1.36		6	174	566	8.37	3.4		4
9.2	10740	104.41	1.58		6	206	480	7.09	3.9		4
						235	419	6.20	4.2		
7.4	13284	196.41	1.27	R 167 RF167	4	68	1455	21.51	0.97	R 87 RF87	4
9.1	10876	160.80	1.56		4	76	1292	19.10	1.05		4
11	8822	130.44	1.91		4	85	1155	17.08	1.13		4
12	8183	120.99	2.07		4	95	1038	15.35	1.21		4
14	7062	104.41	2.4		4	110	902	13.33	1.33		4
16	6232	92.14	2.7		4	122	807	11.93	1.43		4
18	5403	79.88	3.1		4	147	670	9.90	1.66		4
21	4807	71.07	3.5			158	626	9.25	1.82		
						175	563	8.32	1.94		
6.5	15105	146.85	0.81	R 147 RF147	6	202	488	7.22	2.1	RX 157 RXF157	6
8.1	12265	119.24	1.0		6	226	438	6.47	2.2		6
8.7	11318	110.03	1.08		6	272	363	5.36	2.4		6
10	9731	94.60	1.26		6						
12	8586	83.47	1.42		6						
8.9	11056	163.46	1.11	R 147 RF147	4	134	736	10.88	0.84	R 77 RF77	4
10	9932	146.85	1.23		4	151	652	9.64	0.91		4
12	8065	119.24	1.52		4	192	513	7.59	1.12		4
13	7442	110.03	1.64		4	219	450	6.66	1.21		4
15	6398	94.60	1.91		4	248	398	5.88	1.28		4
17	5645	83.47	2.2		4	280	352	5.21	1.36		
20	4876	72.09	2.5		4	191	539	5.05	3.12	RX 157 RXF157	6
22	4508	66.65	2.7		4	209	492	4.68	3.41		6
24	4129	61.50	3.0		4	240	429	4.04	3.92		6
28	3576	52.87	3.4		4						
10	9545	141.12	0.80	R 137 RF137	4	235	437	6.22	3.84	RX 157 RXF157	4
11	8669	128.18	0.87		4						4
13	7691	113.72	0.98		4	249	414	5.88	2.68	RX 127 RXF127	4
14	6980	103.2	1.08		4	277	372	5.28	2.98		4
16	5999	88.70	1.25		4	339	304	4.29	3.65		4
18	5472	80.91	1.37		4	372	277	3.95	4.01		4
20	4970	73.49	1.51		4	281	366	5.19	1.79	RX 107 RXF107	4
22	4410	65.20	1.71		4	314	328	4.65	1.99		4
25	4002	59.17	1.88		4	348	296	4.20	2.63		4
29	3440	50.86	2.2		4	383	269	3.81	2.90		4
33	3002	44.39	2.5		4	432	238	3.38	3.27		4
39	2540	37.65	3.0		4	476	216	3.07	3.60		4
44	2226	32.91	3.4		4	553	186	2.64	4.19		4
23	4383	64.81	0.92	R 107 RF107	4	323	319	4.52	1.75	RX 97 RXF97	4
25	3969	58.69	1.02		4	361	285	4.04	1.96		4
28	3520	52.05	1.15		4	401	257	3.64	2.2		4
31	3183	47.06	1.27		4	442	233	3.30	2.4		4
37	2697	39.88	1.50		4	500	206	2.92	2.7		4
42	2356	34.84	1.72		4	553	186	2.64	3.0		4
48	2059	30.44	1.96		4	652	158	2.24	3.5		4
50	1971	29.14	2.1		4	745	138	1.96	3.9		4
54	1843	27.25	2.2		4	890	116	1.64	4.1		4
59	1664	24.60	2.4		4	1028	110	1.42	4.3		4
65	1511	22.34	2.7		4					RX 87 RXF87	4
74	1341	19.82	3.0		4	420	245	3.48	1.55		4
81	1217	17.99	3.3		4	472	218	3.09	1.75		4
					4	529	195	2.76	1.96		4
34	2889	42.72	0.98		4	589	175	2.48	2.2		4
39	2508	37.08	1.12		4	679	152	2.15	2.4		4
44	2245	33.20	1.21		4	756	136	1.93	2.5		4
53	1863	27.54	1.35	R 97 RF97	4	913	113	1.60	2.6	RX 77 RXF77	4
58	1693	25.03	1.57		4	1050	98	1.39	2.8		4
65	1513	22.37	1.69		4						4
72	1362	20.14	1.80		4	601	171	2.43	1.18		4
80	1234	18.24	1.90		4	685	150	2.13	1.25		4
90	1094	16.17	2.1		4	777	133	1.88	1.33		4
100	989	14.62	2.2		4	874	118	1.67	1.38		4
118	838	12.39	2.5		4	1028	100	1.42	1.46		4

R



输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f _s	机 型 号 Type Type	极 数 Pole p	输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f _s	机 型 号 Type Type	极 数 Pole p
15kW						15kW					
6.1	20783	238	0.81	R 167R107 RF167R107	4	53	2540	27.54	1.1	R 97 RF97	4
6.5	19560	224	0.87		4	58	2309	25.03	1.15		4
7.0	18163	208	0.93			65	2063	22.37	1.24		
7.5	17028	195	0.99			72	1858	20.14	1.32		
8.3	15369	176	1.10			80	1682	18.24	1.40		
7.4	18201	130.44	0.93	R 167 RF167	6	90	1491	16.17	1.51		
8.0	16883	120.99	1.00		6	100	1348	14.62	1.6		
9.2	14569	104.41	1.16			118	1143	12.39	1.8		
11	12857	92.14	1.32			135	999	10.83	2.0		
7.4	18115	196.41	0.93	R 167 RF167	4	158	854	9.26	2.4		
9.1	14830	160.80	1.14		4	174	772	8.37	2.5		
11	12030	130.44	1.41			206	654	7.09	2.9		
12	11159	120.99	1.52			235	572	6.20	3.1		
14	9630	104.41	1.76			85	1575	17.08	0.89	R 87 RF87	4
16	8498	92.14	1.99			95	1416	15.35	0.98		4
18	7367	79.88	2.3			110	1229	13.33	1.05		
21	6555	71.07	2.6			122	1100	11.93	1.13		
23	5901	63.98	2.9			147	913	9.90	1.21		
25	5396	58.51	3.1			158	853	9.25	1.33		
8.8	15353	110.03	0.80	R 147 RF147	6	175	767	8.32	1.42		
10	13200	94.60	0.93		6	202	666	7.22	1.51		
12	11647	83.47	1.05			226	597	6.47	1.61		
13	10059	72.09	1.21			272	494	5.36	1.73		
14	9300	66.65	1.31	R 147 RF147	4	287	488	5.05	3.44	RX 157 RXF157	4
8.9	15076	163.46	0.81		4	315	446	4.68	3.77		4
9.9	13544	146.86	0.90			361	388	4.04	3.32		
12	10997	119.24	1.11			372	378	3.95	2.94	RX 127 RXF127	4
13	10148	110.03	1.20			281	479	5.19	1.36		4
15	8725	94.60	1.40		4	314	429	4.65	1.52	RX 107 RXF107	4
17	7698	83.47	1.59		4	348	387	4.20	2.0		4
20	6649	72.09	1.84			383	351	3.81	2.2		
22	6147	66.65	1.99			432	325	3.38	2.4		
24	5631	61.50	2.2			476	295	3.07	2.6		
28	4876	52.87	2.5			553	254	2.64	3.1		
31	4303	46.65	2.8			635	221	2.30	3.5		
14	9518	103.2	0.8	R 137 RF137	4	749	188	1.95	3.8		
16	8181	88.70	0.92			854	164	1.71	4.0		
18	7462	80.91	1.01			1014	138	1.44	4.4		
20	6778	73.49	1.11			323	435	4.52	1.3	RX 97 RXF97	4
22	6013	65.20	1.25			361	388	4.04	1.4		4
25	5457	59.17	1.38			401	350	3.64	1.6		
29	4691	50.86	1.60			442	317	3.30	1.8		
33	4094	44.39	1.84			500	281	2.92	2.0		
39	3472	37.65	2.2			553	254	2.64	2.2		
44	3035	32.91	2.5			652	215	2.24	2.6		
52	2567	27.83	2.9			745	188	1.96	2.8		
31	4340	47.06	0.9	R 107 RF107	4	890	158	1.64	3.0		
37	3678	39.88	1.10		4	1028	137	1.42	3.1		
42	3213	34.84	1.26			420	335	3.48	1.14	RX 87 RXF87	4
48	2807	30.44	1.44			472	297	3.09	1.28		4
50	2688	29.14	1.50			529	265	2.76	1.43		
54	2513	27.25	1.61			589	238	2.48	1.60		
59	2269	24.60	1.78			679	207	2.15	1.75		
65	2060	22.34	1.96			756	186	1.93	1.80		
74	1828	19.82	2.2			913	154	1.60	1.92		
81	1659	17.99	2.4			1050	134	1.39	2.0		
94	1426	15.46	2.8								
108	1245	13.50	3.2								



输出转速	输出扭矩	传动比	使用系数	机 型 号	极 数	输出转速	输出扭矩	传动比	使用系数	机 型 号	极 数
Output speed	Output torque	Ratio	Service factor	Type	Pole	Output speed	Output torque	Ratio	Service factor	Type	Pole
r/min	Nm	i	f _B	Type	p	r/min	Nm	i	f _B	Type	p
18.5kW						18.5kW					
9.1	18291	160.80	0.93	R 167 RF167	4	110	1516	13.33	0.8	R 87 RF87	4
11	14838	130.44	1.13			122	1357	11.93	0.85		
12	13763	120.99	1.24			147	1126	9.90	0.98		
14	11877	104.41	1.42			158	1052	9.25	1.08		
16	10481	92.14	1.61			175	946	8.32	1.15		
18	9086	79.88	1.86			202	821	7.22	1.22		
21	8084	71.07	2.1			226	736	6.47	1.30		
23	7278	63.98	2.3			272	610	5.36	1.40		
25	6655	58.51	2.5								
29	5791	50.91	2.9								
						317	547	4.68	3.07	RX 157	4
12	13564	119.24	0.90	R 147 RF147	4	364	476	4.04	3.53	RXF157	4
13	12516	110.03	0.98			412	420	3.57	4.0		
15	10761	94.60	1.14			348	478	4.20	1.63	RX 107 RXF107	4
17	9495	83.47	1.29			383	452	3.81	1.73		
20	8200	72.09	1.49			432	401	3.38	1.95		
22	7581	66.65	1.61			476	364	3.07	2.1		
24	6944	61.50	1.76			553	313	2.64	2.5		
28	6014	52.87	2.0			635	273	2.30	2.9		
31	5306	46.65	2.3			749	231	1.95	3.1		
36	4583	40.29	2.7			854	203	1.71	3.3		
				1014	171	1.44	3.6				
18	9203	80.91	0.82	R 137 RF137	4	401	432	3.64	1.30		
20	8359	73.49	0.90			442	391	3.30	1.43		
22	7416	65.20	1.01			500	346	2.92	1.62		
25	6731	59.17	1.12			553	313	2.64	1.79		
29	5785	50.86	1.30			652	266	2.24	2.1		
33	5049	44.39	1.49			745	232	1.96	2.3		
39	4283	37.65	1.76			890	194	1.64	2.4		
44	3744	32.91	2.0			1028	168	1.42	2.5		
49	3362	29.56	2.2								
52	3166	27.83	2.3			529	327	2.76	1.16	RX 87 RXF87	4
61	2730	24.00	2.7			589	294	2.48	1.29		
66	2520	22.15	3.0			679	255	2.15	1.42		
77	2166	19.04	3.5			756	229	1.93	1.46		
87	1911	16.80	3.9			913	190	1.60	1.56		
						1050	165	1.39	1.65		
37	4536	39.88	0.89	R 107 RF107	4	22kW					
42	3963	34.84	1.02			11	17645	130.44	0.95	R 167 RF167	4
50	3315	29.14	1.22			12	16366	120.99	1.04		
59	2798	24.60	1.44			14	14124	104.41	1.20		
65	2541	22.34	1.59			16	12464	92.14	1.36		
74	2255	19.82	1.79			18	10805	79.88	1.57		
81	2046	17.99	1.98			21	9614	71.07	1.76		
94	1759	15.46	2.3			23	8655	63.98	2.0		
108	1536	13.50	2.3			25	7915	58.51	2.1		
128	1302	11.45	3.1			29	6887	50.91	2.5		
146	1139	10.01	3.5			32	6078	44.93	2.8		
181	918	8.07	3.0			37	5269	38.95	3.2		
213	778	6.84	3.6								
72	2291	20.14	1.07	R 97 RF97	4	13	14884	110.03	0.83	R 147 RF147	4
80	2075	18.24	1.13			15	12797	94.60	0.95		
90	1839	16.17	1.23			17	11291	83.47	1.08		
100	1663	14.62	1.30			20	9752	72.09	1.3		
118	1409	12.39	1.46			22	9016	66.65	1.36		
135	1232	10.83	1.59			24	8258	61.50	1.48		
158	1053	9.26	1.81			28	7152	52.87	1.71		
174	952	8.37	2.0			31	6310	46.65	1.94		
206	806	7.09	2.3			36	5450	40.29	2.2		
235	705	6.20	2.5			41	4821	35.64	2.5		
282	589	5.18	2.8			49	4051	29.95	3.0		
328	511	4.49	3.0								

R



输出转速	输出扭矩	传动比	使用系数	机 型 号	极 数	输出转速	输出扭矩	传动比	使用系数	机 型 号	极 数												
Output speed	Output torque	Ratio	Service factor	Type	Pole	Output speed	Output torque	Ratio	Service factor	Type	Pole												
r/min	Nm	i	f _B	Type	p	r/min	Nm	i	f _B	Type	p												
22kW						22kW																	
22	8820	65.20	0.85	R 137 RF137	4	652	316	2.24	1.77	RX 97 RXF97	4												
25	8004	59.17	0.94			745	276	1.96	1.94														
29	6880	50.86	1.09			890	231	1.64	2.05														
33	6005	44.39	1.25			1028	200	1.42	2.14														
39	5093	37.65	1.48			RX 87 RXF87	4	529	389	2.76	0.98												
44	4452	32.91	1.69					589	350	2.48	1.09												
49	3999	29.56	1.88					679	303	2.15	1.19												
52	3765	27.83	2.00					756	272	1.93	1.23												
61	3246	24.00	2.3					913	226	1.60	1.31												
66	2996	22.15	2.5					1050	196	1.39	1.39												
77	2576	19.04	2.9					30kW															
87	2273	16.80	3.3			R 167 RF167	4	16	16996	92.14	1.0												
101	1963	14.51	3.8					18	14735	79.88	1.15												
114	1736	12.83	4.3					21	13109	71.07	1.29												
42	4713	34.84	0.86	R 107 RF107	4			23	11802	63.98	1.43												
								25	10793	58.51	1.57												
								29	9391	50.91	1.80												
								32	8288	44.93	2.04												
								37	7185	38.95	2.4												
								42	6393	34.66	2.6												
								49	5510	29.87	3.1												
								60	4477	24.27	3.8												
								71	3796	20.58	4.5												
								17	15397	83.47	0.8												
								20	13298	72.09	0.92												
						22	12294	66.65	0.99														
						24	11261	61.50	1.09														
						28	9752	52.87	1.25														
31	8605	46.65	1.42																				
36	7432	40.29	1.64																				
41	6574	35.64	1.86																				
49	5525	29.95	2.2																				
60	4462	24.19	2.5																				
71	3770	20.44	3.0																				
81	3328	18.04	3.0																				
93	2885	15.64	4.2																				
72	2724	20.14	1.04	R 97 RF97	4	29	9382	50.86	0.80														
						33	8188	44.39	0.92														
						39	6945	37.65	1.08														
						44	6071	32.91	1.24														
						52	5133	27.83	1.41														
						61	4427	24.00	1.69														
						66	4086	22.15	1.85														
						77	3512	19.04	2.1														
						87	3099	16.80	2.4														
						101	2676	14.51	2.8														
						114	2367	12.83	3.2														
						135	1990	10.79	3.8														
						192	1400	7.59	3.4														
						229	1177	6.38	4.1														
147	1339	9.90	0.83	R 87 RF87	4	74	3656	19.82	1.11														
						81	3318	17.99	1.22														
						94	2852	15.46	1.42														
						108	2490	13.50	1.62														
						128	2112	11.45	1.88														
						146	1846	10.01	1.91														
						173	1561	8.46	2.2														
						181	1489	8.07	2.2														
						213	1262	6.84	2.5														
						244	1103	5.98	2.6														
						289	933	5.06	2.9														
						412	500	3.57	3.36	RX 157 RXF157	4	R 137 RF137	4										
														348	592	4.20	1.32	RX 107 RXF107	4				
																				383	537	3.81	1.45
432	477	3.38	1.64																				
476	433	3.07	1.80																				
553	372	2.64	2.10																				
635	324	2.30	2.41																				
749	275	1.95	2.61																				
854	241	1.71	2.75																				
1014	203	1.44	2.99																				
401	513	3.64	1.09	RX 97 RXF97	4																		
																				442	465	3.30	1.20
																				500	412	2.92	1.36
																				553	372	2.64	1.50



输出转速	输出扭矩	传动比	使用系数	机 型 号	极 数	输出转速	输出扭矩	传动比	使用系数	机 型 号	极 数		
Output speed	Output torque	Ratio	Service factor	Type	Pole	Output speed	Output torque	Ratio	Service factor	Type	Pole		
r/min	Nm	i	f _B	Type	p	r/min	Nm	i	f _B	Type	p		
30kW						37kW							
100	2697	14.62	0.80	R 97 RF97	4	39	8507	37.65	0.88	R 137 RF137	4		
118	2285	12.39	0.90			45	7436	32.91	1.01				
135	1998	10.83	0.98			53	6288	27.83	1.20				
158	1708	9.26	1.12			61	5423	24.00	1.38				
174	1544	8.37	1.24			67	5005	22.15	1.51				
206	1308	7.09	1.44			77	4302	19.04	1.75				
235	1144	6.20	1.55			88	3796	16.80	1.98				
282	955	5.18	1.75			101	3279	14.51	2.3				
325	828	4.49	1.85			115	2899	12.83	2.6				
432	649	3.40	1.71	RX 127 RXF127	4	136	2438	10.79	2.8				
						169	1968	8.71	3.1				
						194	1715	7.59	3.3				
						230	1442	6.38	3.7				
						285	1164	5.15	3.7				
432	623	3.38	1.25	RX 107 RXF107	4	74	4478	19.82	0.90	R 107 RF107	4		
476	566	3.07	1.38			82	4065	17.99	0.99				
553	487	2.64	1.60			95	3493	15.46	1.16				
635	424	2.30	1.84			109	3050	13.50	1.33				
749	360	1.95	2.0			128	2587	11.45	1.50				
854	315	1.71	2.1			147	2262	10.01	1.56				
1014	266	1.44	2.3			174	1912	8.46	1.79				
500	539	2.92	1.04	RX 97 RXF97	4	182	1823	8.07	1.8				
553	487	2.64	1.15			215	1546	6.84	2.1				
652	413	2.24	1.35			246	1351	5.98	2.1				
745	362	1.96	1.48			291	1143	5.06	2.4				
890	303	1.64	1.57										
1028	262	1.42	1.63										
37kW						432	801	3.40	1.39	RX 127 RXF127	4		
18	18049	79.88	0.94	R 167 RF167	4	490	707	3.00	1.57				
21	16058	71.07	1.05			568	610	2.59	1.82				
23	14456	63.98	1.17			435	796	3.38	0.98	RX 107 RXF107	4		
25	13220	58.51	1.28			479	723	3.07	1.08				
29	11503	50.91	1.47			557	622	2.64	1.25				
33	10152	44.93	1.67			639	542	2.30	1.44				
38	8801	38.95	1.92			754	459	1.95	1.57				
42	7831	34.66	2.16			860	403	1.71	1.65				
49	6749	29.87	2.5			1021	339	1.44	1.79				
61	5484	24.27	3.1			45kW							
78	4232	18.73	4.0			23	17463	63.98	0.97	R 167 RF167	4		
90	3685	16.31	4.6			25	15970	58.51	1.06				
101	3290	14.56	5.1			29	13896	50.91	1.22				
						33	12264	44.93	1.38				
						38	10631	38.95	1.59				
						43	9460	34.66	1.79				
				50	8153	29.87	2.08						
				61	6624	24.27	2.4						
				72	5617	20.58	2.6						
				79	5112	18.73	3.0						
				91	4452	16.31	3.4						
				102	3974	14.56	3.5						
22	15060	66.65	0.81	R 147 RF147	4	28	14431	52.87	0.85			R 147 RF147	4
24	13794	61.50	0.89			32	12733	46.65	0.96				
28	11946	52.87	1.02			37	10997	40.29	1.11				
32	10541	46.65	1.16			42	9728	35.64	1.26				
36	9104	40.29	1.34			49	8175	29.95	1.49				
41	8053	35.64	1.52			61	6603	24.19	1.69				
49	6767	29.95	1.81			72	5579	20.44	2.0				
61	5466	24.19	2.0			82	4924	18.04	2.0				
72	4618	20.44	2.4			95	4269	15.64	2.9				
81	4076	18.04	2.4			106	3797	13.91	3.2				
94	3534	15.64	3.5			123	3273	11.99	3.7				
106	3143	13.91	3.8			204	1979	7.25	4.1				

R



输出转速	输出扭矩	传动比	使用系数	机 型 号	极 数	输出转速	输出扭矩	传动比	使用系数	机 型 号	极 数		
Output speed	Output torque	Ratio	Service factor	Type	Pole	Output speed	Output torque	Ratio	Service factor	Type	Pole		
r/min	Nm	i	f _s	Type	p	r/min	Nm	i	f _s	Type	p		
45kW						55kW							
45	8983	32.91	0.84	R 137 RF137	4	78	6352	19.04	1.18	R 137 RF137	4		
53	7596	27.83	0.99			88	5605	16.80	1.34				
62	6551	24.00	1.15			102	4841	14.51	1.55				
67	6046	22.15	1.24			115	4280	12.83	1.76				
78	5197	19.04	1.45			137	3600	10.79	1.90				
88	4586	16.80	1.64			170	2906	8.71	2.1				
102	3960	14.51	1.90			195	2532	7.59	2.3				
115	3502	12.83	2.1			232	2128	6.38	2.5				
137	2945	10.79	2.3			287	1718	5.15	2.5				
170	2377	8.71	2.6										
195	2072	7.59	2.8			415	1242	3.57	1.35	RX 157	4		
232	1741	6.38	3.1			479	1075	3.09	1.56	RXF157	4		
287	1406	5.15	3.1										
						75kW							
96	4220	15.46	0.96	R 107 RF107	4	38	17719	38.95	0.95	R 167 RF167	4		
110	3685	13.50	1.10			43	15767	34.66	1.07				
129	3125	11.45	1.27			50	13588	29.87	1.25				
148	2732	10.01	1.29			61	11041	24.27	1.43				
175	2309	8.46	1.48			72	9362	20.58	1.53				
183	2203	8.07	1.50			79	8521	18.73	1.81				
216	1867	6.84	1.71			91	7420	16.31	2.03				
247	1632	5.98	1.75			102	6624	14.56	2.13				
292	1381	5.06	2.0			119	5646	12.41	3.0				
						144	4677	10.28	3.4				
435	968	3.40	1.15	RX 127 RXF127	4	169	3990	8.77	4.0				
493	854	3.00	1.30										
571	737	2.59	1.51			49	13625	29.95	0.90	R 147 RF147	4		
646	652	2.29	1.70			61	11004	24.19	1.11				
767	549	1.93	2.02			72	9298	20.44	1.20				
						82	8207	18.04	1.21				
438	962	3.38	0.81	RX 107 RXF107	4	95	7115	15.64	1.72				
482	874	3.07	0.89			106	6328	13.91	1.87				
561	751	2.64	1.04			123	5454	11.99	2.2				
643	654	2.30	1.19			152	4431	9.74	2.5				
759	555	1.95	1.30			179	3758	8.26	2.8				
865	487	1.71	1.36			204	3298	7.25	3.0				
1028	410	1.44	1.48			251	2679	5.89	3.3				
						296	2275	5.00	3.6				
						479	1466	3.09	1.15	RX 157 RXF157	4		
						538	1304	2.75	1.29				
						624	1124	2.37	1.49				
						767	915	1.93	1.84				
						767	915	1.93	1.21	RX 127 RXF127	4		
						949	740	1.56	1.50				
						90kW							
						43	18921	34.66	0.89	R 167 RF167	4		
						50	16306	29.87	1.04				
						61	13249	24.27	1.20				
						72	11235	20.58	1.28				
						79	10225	18.73	1.51				
						91	8904	16.31	1.69				
						102	7947	14.56	1.77				
						119	6775	12.41	2.5				
						144	5612	10.28	2.8				
						169	4788	8.77	3.3				
32	15563	46.65	0.8	R 147 RF147	4								
37	13441	40.29	0.91										
42	11890	35.64	1.03										
49	9991	29.95	1.22										
61	8070	24.19	1.39										
72	6819	20.44	1.65										
82	6018	18.04	1.64										
95	5218	15.64	2.3										
106	4640	13.91	2.6										
123	4000	11.99	3.1										
152	3249	9.74	3.8										
204	2419	7.25	3.4										
251	1965	5.89	4.1										

R



输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f_B	机 型 号 Type Type	极 数 Pole p	输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f_B	机 型 号 Type Type	极 数 Pole p
90kW											
72	11158	20.44	1.01								
82	9848	18.04	1.10								
95	8538	15.64	1.43								
106	7593	13.91	1.56	R 147	4						
123	6545	11.99	1.87	RF147	4						
156	5170	9.47	2.1								
179	4509	8.26	2.4								
204	3958	7.25	2.5								
251	3215	5.89	2.7								
296	2729	5.00	3.0								
542	1555	2.75	1.08	RX 157	4						
629	1340	2.37	1.25	RXF157	4						
772	1091	1.93	1.54								
955	882	1.56	1.26	RX 127	4						
				RXF127	4						
110kW											
61	16193	24.27	1.04								
72	13731	20.58	1.23								
91	10882	16.31	1.38	R 167	4						
102	9715	14.56	1.45	RF167	4						
119	8280	12.41	2.04								
144	6859	10.28	2.3								
169	5851	8.77	2.7								
629	1638	2.37	1.03	RX 157	4						
772	1334	1.93	1.26	RXF157	4						
914	1126	1.63	1.49								
132kW											
72	16477	20.58	1.03								
91	13059	16.31	1.15								
102	11657	14.56	1.21	R 167	4						
119	9936	12.41	1.70	RF167	4						
144	8231	10.28	1.94								
169	7022	8.77	2.28								
914	1351	1.63	1.24	RX 157	4						
				RXF157	4						
160kW											
120	11963	12.41	1.41	R 167	4						
145	9910	10.28	1.61	RF167	4						
170	8484	8.77	1.89								

R



Mamax Permissible torque Nm	输出转速 Output speed r/min	传动比 Ratio i	机 型 号 Type Type	功率 Power kW/4p	Mamax Permissible torque Nm	输出转速 Output speed r/min	传动比 Ratio i	机 型 号 Type Type	功率 Power kW/4p	
130	8.5	164	R 27R17 RF27R17	0.18	1550	0.82	1690	R 87R57 RF87R57	0.18	
	8.9	156				0.91	1524			
	10	135		0.25		1.0	1395		0.25	
	12	118				1.1	1232			
	13	104				1.2	1145			
15	90	1.3	1037							
200	4.8	289	R 37R17 RF37R17	0.18		1.6	883		R 87R57 RF87R57	0.37
	5.7	243				1.7	802			
	6.2	226		0.25		1.8	754			0.55
	7.5	185				1.4	1008			
	8.5	164				2.0	683			
	8.9	156				2.3	599			
	10	135				2.6	538			
11	127	2.9	472							
300	13	104	R 47R37 RF47R37	0.37		3.4	400		0.75	
	15	90			3.5	396				
	3.2	429		0.18	3.9	361	1.1			
	3.7	372			4.0	351				
	4.0	348			0.25	4.6		305		0.18
	4.6	301				4.7		300		
5.5	255	5.2	267							
6.1	228	5.5	256							
450	2.1	678	R 57R37 RF57R37	0.18	3000	0.32	4309	R 97R57 RF97R57	0.18	
	2.4	589				0.35	4004			
	2.6	537		0.25		0.38	3702		0.37	
	3.0	471				0.40	3481			
	3.9	357				0.46	3019			
	4.4	319				0.52	2668			
5.2	267	0.37	0.62	2245		0.25				
5.8	241		0.69	2016						
600	1.7		836	R 67R37 RF67R37			0.18		0.76	1823
	1.9	750	0.80			1733				
	2.0	730	0.86			1623				
	2.2	630	0.88			1583				
	2.4	571	0.97			1434				
	2.5	561	1.00			1396				
	2.8	495	0.25			1.1	1228		0.75	
	2.9	486			1.2	1207				
	3.2	438			1.3	1084				
3.6	388	1.3		1068						
820	4.1	336	R 77R37 RF77R37	0.37	1.5	937	1.5			
	4.8	287			1.5	934				
	1.2	1124			1.6	878		2.2		
	1.3	1047			1.7	824				
	1.5	915			1.8	755				
	1.6	858		1.9	737					
	1.8	757		0.18	2.1	631			1.1	
	2.1	671			2.2	625				
	2.4	571			2.5	549				
	2.5	547			2.6	560				
2.9	477	2.9	484							
1550	3.3	426	R 87R57 RF87R57	0.18	3.2	430	0.25			
	3.8	364			3.7	379				
	4.5	312			4.1	336				
	4.5	310			4.7	296				
	5.6	248			5.1	270				
	0.65	2129			5.6	249				
	0.71	1955			5.9	234				
0.72	1930	6.1	227							
0.79	1737									
0.80	1733									

表上所配功率均有超载,按实际条件确定的转扭不得大于减速机额定转扭。

The power are all overload in the table. The decided torque according to operating condition should not more than gear units' nominal torque.



Mamax	输出转速	传动比	机 型 号	功率	Mamax	输出转速	传动比	机 型 号	功率
Permissible torque	Output speed	Ratio	Type	Power	Permissible torque	Output speed	Ratio	Type	Power
Nm	r/min	i	Type	kW/4p	Nm	r/min	i	Type	kW/4p
4300	0.21	6690	R 107R77 RF107R77	0.18	8000	0.34	4018	R 137R77 RF137R77	0.37
	0.24	5735				0.35	3928		
	0.27	5127				0.40	3514		
	0.32	4302				0.41	3377		
	0.36	3870				0.42	3338		
	0.36	3847		0.25		0.47	2929		0.55
	0.42	3302				0.48	2926		
	0.46	3015				0.52	2658		
	0.46	2997				0.56	2484		
	0.53	2621				0.58	2412		
	0.62	2252		0.37		0.62	2242		0.75
	0.68	2041				0.67	2073		
	0.71	1971				0.75	1863		
	0.77	1813				0.76	1839		
	0.83	1673				0.88	1598		
	0.88	1587		0.55		1.0	1397		1.1
	0.91	1531				1.1	1226		
	1.00	1390				1.3	1090		
	1.00	1389				1.3	1080		
	1.14	1216				1.4	1020		
	1.2	1194		0.75		1.5	951		1.5
	1.27	1095				1.6	869		
	1.3	1043				1.7	831		
	1.50	927				2.0	730		
	1.6	888				2.1	684		
	1.7	787		1.1		2.3	629		2.2
	2.0	692				2.3	609		
	2.3	605				2.6	564		
	2.4	598				2.6	549		
	2.6	530				2.8	517		
	2.7	510		1.5		2.9	490		3
	2.9	479				3.2	453		
	3.1	463				3.4	428		
	3.4	420				3.8	376		
	3.5	406				3.8	374		
	3.8	373		2.2		4.2	339		4
	4.0	357				4.5	317		
	4.5	321				4.8	297		
	4.6	313				5.0	286		
	5.1	281				5.8	250		
	5.2	277		3		0.08	18210		0.18
	5.7	253				0.09	15923		
	5.8	245				0.10	14075		
	6.6	217				0.12	12344		
	6.9	208				0.13	11143		
7.5	191	4	0.15	9743	0.25				
7.9	181		0.17	8443					
8.6	167		0.20	7307					
8000	0.12		11712	13000		0.22	6447	R 147R77 RF147R77	0.37
	0.13		10573			0.26	5568		
	0.16	8784	0.30		4815				
	0.19	7479	0.33		4325				
	0.22	6412	0.39		3669				
	0.24	5834	0.44		3228	0.75			
	0.28	5001	0.50		2833				
	0.30	4709							
	0.32	4364							

表上所配功率均有超载,按实际条件确定的转扭不得大于减速机额定转扭。



The power are all overload in the table.The decided torque according to operating condition should not more than gear units' nominal torque.





Mamax Permissible torque Nm	输出转速 Output speed r/min	传动比 Ratio i	机 型 号 Type Type	功率 Power kW/4p	Mamax Permissible torque Nm	输出转速 Output speed r/min	传动比 Ratio i	机 型 号 Type Type	功率 Power kW/4p
13000	0.56	2555	R 147R77 RF147R77	1.1	4.9 5.1 5.2 5.6 6.1 6.5 7.0 7.5	295 287 281 260 238 224 208 195	R 167R107 RF167R107	11 15	
	0.65	2211							
	0.73	1951							
	0.84	1705		1.5					
	0.93	1536							
	1.1	1329							
	1.2	1166		2.2					
	1.4	1029							
	1.6	889	3						
	1.8	784							
	2.1	695		4					
	2.4	607							
	2.6	547							
	3.0	480	5.5						
	2.7	540							
	3.1	462		5.5					
	3.3	432							
	3.9	373	7.5						
4.4	330								
6.8	216	11							
18000	0.05	27001	R 167R97 RF167R97	0.55					
	0.06	22482							
	0.07	20002							
	0.08	17361							
	0.09	15446							
	0.10	14051							
	0.12	11812							
	0.13	10519							
	0.14	9754							
	0.23	6069							
	0.26	5399		0.75					
	0.30	4709							
	0.33	4182							
	0.18	7749		1.1					
	0.20	6894							
	0.37	3739							
	0.54	2657		1.5					
	0.61	2333							
	0.69	2085							
	0.76	1877		2.2					
	0.86	1670							
	0.98	1456							
	1.1	1296		3					
	1.3	1137							
	1.4	1012							
	1.7	872		4					
	1.9	770							
	2.2	664		5.5					
	2.5	578							
	2.8	510		7.5					
	3.3	438							
	3.8	380							
	4.3	338							
	4.8	307							
	5.2	282		11					

表上所配功率均有超载,按实际条件确定的转矩不得大于减速机额定转矩。

The power are all overload in the table. The decided torque according to operating condition should not more than gear units' nominal torque.

**RX..S37**

电机需方配时或配特殊电机时需加联接法兰
When equipping the user's motor or the special one, the flange is required to connected.




注：其余尺寸见相应的结构形式
Note: For other values please refer to the oppsited structure

Y2电机机座号 Motor size	63	71		80		90S	
功率/4P Power/(kW)	0.18	0.25	0.37	0.55	0.75	1.1	
L3	223	236		264		301	
G	130	145		175		195	
L2	71	71		71		71	


Note:"RX.."mean RX、RXF



RX57




RX..S57




RXF57


Φ140




Φ160



Φ200



电机需方配时或配特殊电机时需加联接法兰
When equipping the user's motor or the special one, the flange is required to be connected.



注：其余尺寸见相应的结构形式
Note: For other values please refer to the opposite structure


Y2电机机座号 Motor size	63	71	80	90S	90L	100	112M	132S	
功率/4P Power/(kW)	0.18	0.25 0.37	0.55 0.75	1.1	1.5	2.2 3.0	4.0	5.5	
L3	223	245	278	304	328	350	380	425	
G	130	145	175	195	195	215	240	275	
L2	81	81	81	81	81	93	93	101	

注：“RX..”表示RX、RXF


Note:“RX..”mean RX、RXF




RX67



RX..S67





RXF67




电机需方配时或配特殊电机时需加联接法兰
When equipping the user's motor or the special one, the flange is required to be connected.

R



注：其余尺寸见相应的结构形式
Note: For other values please refer to the opposite structure




Y2电机座号 Motor size	63	71		80		90S	90L	100		112M	132S	132M	
功率/4P Power/(kW)	0.18	0.25	0.37	0.55	0.75	1.1	1.5	2.2	3.0	4.0	5.5	7.5	
L3	223	245		278		304	328	350		380	425	461	
G	130	145		175		195	195	215		240	275	275	
L2	81	81		81		81	81	93		93	101	101	

注：“RX..”表示RX、RFX

Note:“RX..”mean RX、RFX





Mounting Dimension Sheets-overview

[illegible]


Technical drawing of a mechanical part, likely a pump or valve component, showing dimensions: 140, 50, 24k6, 200, and M8.





Φ 200



电机需方配时或配特殊电机时需加联接法兰
When equipping the user's motor or the special one, the flange is required to connected.



Φ 250



注：其余尺寸见相应的结构形式
Note: For other values please refer to the oppsited structure


Y ₂ 电机机座号 Motor size	90S	90L	100		112M	132S	132M	160M
功率/4P Power/(kW)	1.1	1.5	2.2	3.0	4.0	5.5	7.5	11
L3	304	328	350		380	425	461	524
G	195	195	215		240	275	275	330
L2	81	81	93		93	101	101	126

注:“RX..”表示RX、RXF



Note: "RX.."mean RX, RXF



RX87




RX..S87



RXF87


Φ250




电机需方配时或配特殊电机时需加联接法兰
When equipping the user's motor or the special one, the flange is required to be connected.

R

Φ300



注：其余尺寸见相应的结构形式
Note: For other values please refer to the oppsited structure




Y ₂ 电机机座号 Motor size	100	112M	132S	132M	160M	160L	180M	180L	
功率/4P Power/(kW)	3.0	4.0	5.5	7.5	11	15	18.5	22	
L3	351	380	425	461	524	547	583	616	
G	215	240	275	275	330	330	380	380	
L2	71	71	101	101	126	126	126	126	


注：“RX..”表示RX、RXF
Note: "RX.."mean RX、RXF




RX97




RX..S97



RXF97



电机需方配时或配特殊电机时需加联接法兰
When equipping the user's motor or the special one, the flange is required to be connected.




注：其余尺寸见相应的结构形式
Note: For other values please refer to the oppsited structure

Y ₂ 电机座号 Motor size	132S	132M	160M	160L	180M	180L	200	
功率/4P Power/(kW)	5.5	7.5	11	15	18.5	22	30	
L3	425	461	524	547	555	588	654	
G	275	275	330	330	380	380	420	
L2	101	101	126	126	126	126	126	


注：“RX..”表示RX、RXF
Note:“RX..”mean RX、RXF




RX107



RX..S107




RXF107



电机需方配时或配特殊电机时需加联接法兰
When equipping the user's motor or the special one, the flange is required to be connected.

R




注：其余尺寸见相应的结构形式
Note: For other values please refer to the oppsited structure

Y ₂ 电机机座号 Motor size	132M	160M	160L	180M	180L	200	225S	225M	
功率/4P Power/(kW)	7.5	11	15	18.5	22	30	37	45	
L3	422	504	519	555	588	654	680	702	
G	275	330	330	380	380	420	470	470	
L2	101	126	126	126	126	132	132	132	


注：“RX..”表示RX、RXF
Note: "RX.."mean RX、RXF



RX127





RX..S127



电机需方配时或配特殊电机时需加联接法兰
When equipping the user's motor or the special one, the flange is required to be connected.


RXF127




注：其余尺寸见相应的结构形式
Note: For other values please refer to the oppsited structure

Y2电机机座号 Motor size	132M	160M	160L	180M	180L	200	225S	225M	250	280S	280M
功率/4P Power/(kW)	7.5	11	15	18.5	22	30	37	45	55	75	90
L3	424	567	602	583	616	654	674	696	775	845	845
G	275	330	330	380	380	420	470	470	510	580	580
L2	132	132	132	132	132	132	143	143	120	120	120

RX157





RX..S157



电机需方配时或配特殊电机时需加联接法兰
When equipping the user's motor or the special one, the flange is required to be connected.

RXF157



注：其余尺寸见相应的结构形式
Note: For other values please refer to the oppsited structure


Y2电机机座号 Motor size	160M	160L	180M	180L	200	225S	225M	250	280S	280M	315S	315M
功率/4P Power/(kW)	11	15	18.5	22	30	37	45	55	75	90	110	132
L3	567	602	635	666	642	669	691	770	828	879	1100	1130
G	330	330	380	380	420	470	470	510	580	580	645	645
L2	143	143	143	143	143	143	143	143	143	143	145	145

注：“RX..”表示RX、RFX


Note: "RX.."mean RX、RFX




RX187



RX..S187



电机需方配时或配特殊电机时需加联接法兰
When equipping the user's motor or the special one, the flange is required to be connected.



注：其余尺寸见相应的结构形式
Note: For other values please refer to the oppsited structure


Y ₂ 电机机座号 Motor size	160M	160L	180M	180L	200	225S	225M	250	280S	280M	315S	315M
功率/4P Power/(kW)	11	15	18.5	22	30	37	45	55	75	90	110	132
L3	567	602	635	666	642	669	691	770	828	879	1100	1130
G	330	330	380	380	420	470	470	510	580	580	645	645
L2	143	143	143	143	143	143	143	143	143	143	145	145

注：“RX..”表示RX、RXF


Note: "RX.." mean RX、RXF




R17



电机需方配时或配特殊电机时需加联接法兰
When equipping the user's motor or the special one, the flange is required to be connected.



RF17



注：其余尺寸见相应的结构形式
Note: For other values please refer to the opposite structure

R


Y2电机机座号 Motor size	63	71	80							
功率/4P Power/(kW)	0.18	0.25 0.37	0.55 0.75							
L3	235	245	278							
G	130	145	175							
L2	71	71	71							

注：“R..”表示R、RF


Note: "R.." mean R, RF




R27




电机需方配时或配特殊电机时需加联接法兰
When equipping the user's motor or the special one, the flange is required to be connected.




RF27



R..S27



R..27R17



注：其余尺寸见相应的结构形式
Note: For other values please refer to the opposite structure


Y2电机机座号 Motor size	63	71	80	90S	90L	100	
功率/4P Power/(kW)	0.18	0.25 0.37	0.55 0.75	1.1	1.5	2.2 3.0	
L3	235	245	278	304	328	340	
G	130	145	175	195	195	215	
L2	71	71	71	71	71	93	

注：“R..”表示R、RF


Note:“R..”mean R、RF




R37




电机需方配时或配特殊电机时需加联接法兰
When equipping the user's motor or the special one, the flange is required to be connected.




RF37



R..S37



R..37R17



注：其余尺寸见相应的结构形式
Note: For other values please refer to the opposite structure


Y2电机机座号 Motor size	63	71		80		90S	90L	100L		
功率/4P Power/(kW)	0.18	0.25	0.37	0.55	0.75	1.1	1.5	2.2	3.0	
L3	235	245		278		304	328	340		
G	130	145		175		195	195	215		
L2	71	71		71		71	71	93		

注：“R..”表示R、RF


Note: "R.." mean R、RF




R47





电机需方配时或配特殊电机时需加联接法兰
When equipping the user's motor or the special one, the flange is required to be connected.




RF47



R..S47



R..47R37



注：其余尺寸见相应的结构形式
Note: For other values please refer to the opposite structure


Y2电机机座号 Motor size	63	71	80	90S	90L	100	112M	132S	
功率/4P Power/(kW)	0.18	0.25 0.37	0.55 0.75	1.1	1.5	2.2 3.0	4.0	5.5	
L3	223	245	278	304	328	350	380	425	
G	130	145	175	195	195	215	240	275	
L2	81	81	81	81	81	93	93	101	

注：“R..”表示R、RF


Note: "R.." mean R、RF



R57




电机需方配时或配特殊电机时需加联接法兰
When equipping the user's motor or the special one, the flange is required to connected.




RF57


Φ200




R..S57



Φ250



R..57R37



注：其余尺寸见相应的结构形式
Note: For other values please refer to the oppsited structure


Y2电机机座号 Motor size	63	71	80	90S	90L	100L	112M	132S	132M	
功率/4P Power/(kW)	0.18	0.25 0.37	0.55 0.75	1.1	1.5	2.2 3.0	4.0	5.5	7.5	
L3	223	245	278	304	328	350	380	425	461	
G	130	145	175	195	195	215	240	275	275	
L2	81	81	81	81	81	93	93	101	101	

注：“R..”表示R、RF


Note:“R..”mean R、RF



R67




电机需方配时或配特殊电机时需加联接法兰
When equipping the user's motor or the special one, the flange is required to be connected.




RF67


Φ200




R..S67



Φ250



R..67R37



注：其余尺寸见相应的结构形式
Note: For other values please refer to the opposite structure


Y2电机机座号 Motor size	63	71	80	90S	90L	100L	112M	132S	132M	
功率/4P Power/(kW)	0.18	0.25 0.37	0.55 0.75	1.1	1.5	2.2 3.0	4.0	5.5	7.5	
L3	223	245	278	304	328	350	380	425	461	
G	130	145	175	195	195	215	240	275	275	
L2	81	81	81	81	81	93	93	101	101	

注：“R..”表示R、RF


Note: "R.." mean R、RF



R77




电机需方配时或配特殊电机时需加联接法兰
When equipping the user's motor or the special one, the flange is required to connected.




RF77


Φ250




R..S77



Φ300



R..77R37



注：其余尺寸见相应的结构形式
Note: For other values please refer to the oppsited structure


Y2电机机座号 Motor size	63	71		80		90S	90L	100L		112M	132S	132M	160M
功率/4P Power/(kW)	0.18	0.25	0.37	0.55	0.75	1.1	1.5	2.2	3.0	4.0	5.5	7.5	11
L3	223	233		278		304	328	350		380	425	461	524
G	130	145		175		195	195	215		240	275	275	330
L2	81	81		81		81	81	93		93	101	101	126

注：“R..”表示R、RF


Note:“R..”mean R、RF



R87




电机需方配时或配特殊电机时需加联接法兰
When equipping the user's motor or the special one, the flange is required to be connected.




RF87


Φ300




R..S87



Φ350



R..87R57



注：其余尺寸见相应的结构形式
Note: For other values please refer to the opposite structure


Y2电机机座号 Motor size	80		90S	90L	100		112M	132S	132M	160M	160L	180M	180L
功率/4P Power/(kW)	0.55	0.75	1.1	1.5	2.2	3.0	4.0	5.5	7.5	11	15	18.5	22
L3	246		280	304	350		380	425	461	524	547	583	616
G	175		195	195	215		240	275	275	330	330	380	380
L2	86		86	86	71		71	101	101	126	126	126	126

注：“R..”表示R、RF


Note:“R..”mean R、RF



R97




电机需方配时或配特殊电机时需加联接法兰
When equipping the user's motor or the special one, the flange is required to connected.




RF97


Φ350




R..S97



Φ450



R..97R57



注：其余尺寸见相应的结构形式
Note: For other values please refer to the oppsited structure


Y ₂ 电机机座号 Motor size	80	90S	90L	100	112M	132S	132M	160M	160L	180M	180L	200	
功率/4P Power/(kW)	0.55 0.75	1.1	1.5	2.2 3.0	4.0	5.5	7.5	11	15	18.5	22	30	
L3	246	280	304	315	334	425	461	524	547	555	588	654	
G	175	195	195	215	240	275	275	330	330	380	380	420	
L2	86	86	86	101	101	101	101	126	126	126	126	132	

注：“R..”表示R、RF


Note:“R..”mean R、RF



R107




电机需方配时或配特殊电机时需加联接法兰
When equipping the user's motor or the special one, the flange is required to be connected.




RF107


Φ350




R..S107



Φ450



R..107R77




注：其余尺寸见相应的结构形式
Note: For other values please refer to the opposite structure

Y2电机机座号 Motor size	100	112M	132S	132M	160M	160L	180M	180L	200	225S	225M	
功率/4P Power/(kW)	2.2 3.0	4.0	5.5	7.5	11	15	18.5	22	30	37	45	
L3	318	334	386	422	504	519	555	588	654	680	702	
G	215	240	275	275	330	330	380	380	420	470	470	
L2	101	101	101	101	126	126	126	126	132	132	132	


注：“R..”表示R、RF

Note:“R..”mean R、RF




Mounting Dimension Sheets-overview



Technical drawing of the 1000W motor assembly. The main view shows the motor with dimensions: 589 (total length), 170 (flange width), 400 (motor body diameter), 25.1 (internal feature), 410 (base width), 490 (total base width), 50 (base height), and L3 (total length including base). A detail view of the flange shows a diameter of $\phi 90m6$, a hole diameter of M24, and a thickness of 25. The base diameter is $\phi 95$.




电机需方配时或配特殊电机时需加联接法兰
When equipping the user's motor or the special one, the flange is required to connected.





Φ 450




R..S137



Φ 550



R..137R77



注：其余尺寸见相应的结构形式
Note: For other values please refer to the oppsited structure


Y2电机机座号 Motor size	132S	132M	160M	160L	180M	180L	200	225S	225M	250	
功率/4P Power/(kW)	5.5	7.5	11	15	18.5	22	30	37	45	55	
L3	388	424	476	519	555	588	654	680	702	771	
G	275	275	330	330	380	380	420	470	470	510	
L2	126	126	132	132	132	132	132	143	143	174	

注：“R..”表示R、RF


Note:"R.."mean R、RF



R147




电机需方配时或配特殊电机时需加联接法兰
When equipping the user's motor or the special one, the flange is required to be connected.




RF147


Φ450




R..S147



Φ550



R..147R87(R77)



	R..147R77组合	R..147R87组合
L	220	272

注：其余尺寸见相应的结构形式
Note: For other values please refer to the oppsited structure


Y2电机机座号 Motor size	160M	160L	180M	180L	200	225S	225M	250	280S	280M	
功率/4P Power/(kW)	11	15	18.5	22	30	37	45	55	75	90	
L3	567	602	583	616	654	674	696	775	845	845	
G	330	330	380	380	420	470	470	510	580	580	
L2	132	132	132	132	132	143	143	174	174	174	

注：“R..”表示R、RF


Note:“R..”mean R、RF



R167




电机需方配时或配特殊电机时需加联接法兰
When equipping the user's motor or the special one, the flange is required to connected.




RF167


Φ550




R..S167



Φ660



R..167R97(R107)



	R..167R97组合	R..167R107组合
L	320	361

注：其余尺寸见相应的结构形式
Note: For other values please refer to the oppsited structure

Y2电机座号 Motor size	160M	160L	180M	180L	200	225S	225M	250	280S	280M	315S	315M	315L
功率/4P Power/(kW)	11	15	18.5	22	30	37	45	55	75	90	110	132	160
L3	567	602	635	666	642	669	691	770	828	879	1100	1130	1360
G	330	330	380	380	420	470	470	510	580	580	645	645	645
L2	143	143	143	143	143	143	143	113	113	113	113	145	145

注：“R..”表示R、RF

Note:“R..”mean R、RF